

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 24 S., R. 7 W.

CHAINS

40.27

Point for the  $\frac{1}{4}$  sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$   
 S 5 | S 4  
 T 24 S | R 7 W  
 1963

from which

A fir, 20 ins. diam., bears N.  $5^\circ$  E., 45 lks. dist., mkd.  $\frac{1}{4}$  S4 BT.

A fir, 6 ins. diam., bears S.  $88^\circ$  W., 43 lks. dist., mkd.  $\frac{1}{4}$  S5 BT.

Descend 50 ft. over NE. slope.

42.30

Bottom of descent, slopes E.; asc. 55 ft. over SE. slope.

46.30

Spur, slopes E.; desc. 380 ft. over NE. slope.

68.55

Creek, 10 lks. wide, course NW.; asc. 120 ft. over SW. slope.

76.59

Intersect the S. bdy. of T. 23 S., R. 7 W., and true point for the closing corner of secs. 4 and 5.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 S R 7 W  
 S 32  
 S 5 | S 4  
 CC  
 T 24 S R 7 W  
 1963

FD. OK 2/80  
 L. ROBERTS  
 M 84-57

from which

A fir, 6 ins. diam., bears S.  $73\frac{1}{2}^\circ$  E., 55 lks. dist., mkd. T24S R7W S4 CC BT.

A fir, 12 ins. diam., bears S.  $79^\circ$  W., 27 lks. dist., mkd. T24S R7W S5 CC BT on double blaze.

From this point the original closing corner of secs. 4 and 5, bears N.  $0^\circ 17'$  E., 0.13 chs. dist., perpetuated and recorded by Deputy County Surveyor, James W. Byron, in 1960, monumented with an iron post, 1 in. diam., firmly set, protruding 12 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE  
 T 23 S R 7 W  
 CC  
 S 5 | S 4  
 T 24 S  
 1960

from which the remains of the original bearing trees

A fir, 50 ins. diam., bears S.  $36^\circ$  E., 80 lks. dist., mkd. with illegible scribe marks on bark blaze.