

Dependent Resurvey, Subdivisional Lines, T. 24 S., R. 7 W.

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.

$$\frac{\frac{1}{4} S 5}{S 8}$$

T 24 S R 7 W
1963

from which

A fir, 8 ins. diam., bears N. 45° E., 83 lks. dist., mkd. ¼ S5 BT.

A fir, 20 ins. diam., bears S. 24½° E., 65 lks. dist., mkd. ¼ S8 BT.

Ascend 410 ft. over E. slope, changing to SE. slope.

40.35 Dirt road, 15 lks. wide, bears N. 30° E. and S. 30° W., curving W.

44.25 Same road, bears N. 30° W., curving SW., and S. 30° E.

45.25 Same road, bears NE. and SW.

51.35 Same road, bears NW. and SE.

51.55 Same road, bears NE. and S. 30° W.

55.80 Enter old logged area, edge bears W. and S.

69.80 Spur ridge, bears NE. and SW.; desc. 150 ft. over NW. slope.

80.50 The cor. of secs. 5, 6, 7, and 8, perpetuated and recorded by Deputy County Surveyor, James W. Byron, in 1960, monumented with an iron post, 1 in. diam., firmly set, protruding 12 ins. above the ground, with brass cap mkd.

$$\begin{array}{c} T 24 S R 7 W \\ \frac{S 6 | S 5}{S 7 | S 8} \\ 1960 \end{array}$$

from which the original bearing trees

A rotted fir snag, 50 ins. diam., bears N. 85° E., 28 lks. dist., 25 lks. dist. to face, no marks remaining. (Record, 25 lks.)

A down fir, 60 ins. diam., bears S. 20° E., 59 lks. dist., mkd. T24S R7W S8 on bark blaze.

A down fir, 33 ins. diam., bears S. 2° W., 100 lks. dist., mkd. with illegible bark scribing.

A sawed fir stump, 30 ins. diam., bears N. 35° W., 32 lks. dist., 30 lks. dist. to face, no marks visible. (Record, 30 lks.)

and bearing trees mkd. by Byron

A hemlock, 15 ins. diam., bears N. 43° E., 42 lks. dist., mkd. T24S R7W S5 CS BT on double blaze.

A chinquapin, 17 ins. diam., bears S. 19° E., 30 lks. dist., mkd. T24S R7W S8 CS BT on double blaze.