

County Surveyor's Record, Douglas County, Oregon

Subdivision of Sec. 5, T. 24 S., R. 7 W.

CHAINS

- 2.60 Spur ridge, bears NW. and SE.; desc. 205 ft. over W. slope.
- 8.20 Dirt road, 20 lks. wide, bears SE. and S. 80° W., also a fence bears N. and S.
- 19.40 Dirt road, 15 lks. wide, bears S. 80° E. and NW. curving N.
- 19.60 Barbed wire fence, bears N. and S., enter dense timber and moderate undergrowth.
- 20.17 Point for the center E $\frac{1}{16}$ sec. cor. of sec. 5.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd.
- E $\frac{1}{16}$
C ————— C
S 5
1963
- from which
- A fir, 12 ins. diam., bears N. $1\frac{1}{2}^\circ$ E., 28 lks. dist., mkd. CE $\frac{1}{16}$ S5 BT.
- A fir, 14 ins. diam., bears S. $47\frac{1}{4}^\circ$ W., 61 lks. dist., mkd. CE $\frac{1}{16}$ S5 BT.
- Descend 185 ft. over SW. slope.
- 28.80 Creek, 6 lks. wide, course N. 10° W.; asc. 195 ft. over E. slope.
- 31.55 Dirt road, 20 lks. wide, bears N. and S.
- 39.30 Spur, slopes N.; desc. 5 ft. over W. slope.
- 40.34 The center $\frac{1}{4}$ sec. cor. of sec. 5.
Descend 100 ft. over W. slope, changing to NW. slope.
- 58.50 Creek, 3 lks. wide, course N. 30° W.; asc. 60 ft. over NE. slope.
- 60.43 Point for the center W $\frac{1}{16}$ sec. cor. of sec. 5.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- W $\frac{1}{16}$
C ————— C
S 5
1963
- from which
- A fir, 20 ins. diam., bears N. 10° W., 51 lks. dist., mkd. CW $\frac{1}{16}$ S5 BT.
- A hemlock, 10 ins. diam., bears S. $24\frac{1}{4}^\circ$ W., 17 lks. dist., mkd. CW $\frac{1}{16}$ S5 BT.
- From this point an iron pipe, $\frac{3}{4}$ in. diam., protruding 18 ins. above the ground, bears S. $81^\circ 02'$ E., 19 lks. dist.
- Ascend 55 ft. over E. slope.