

County Surveyor's Record, Douglas County, Oregon

Subdivision of Sec. 5, T. 24 S., R. 7 W.

CHAINS	
64.00	Spur, slopes N.; desc. 5 ft. along broken N. slope.
68.80	Spur, slopes N.; desc. 55 ft. over W. slope.
70.80	Creek, 1 lk. wide, course N.; asc. 80 ft. over E. slope.
72.60	Spur, slopes N.; desc. 100 ft. over W. slope.
76.00	Creek, 4 lks. wide, course NE.; asc. 75 ft. over SE. slope.
80.52	The $\frac{1}{4}$ sec. cor. of secs. 5 and 6.
	From the E $\frac{1}{16}$ sec. cor. of secs. 5 and 8. N. $0^{\circ} 17' E.$, on the N. and S. center line of the $SE\frac{1}{4}$ of sec. 5. Descend 65 ft. over N. slope, through moderate timber and undergrowth.
2.75	Creek, 1 lk. wide, course W.; asc. 80 ft. over S. slope.
10.15	Spur, slopes W.; desc. 180 ft. over N. slope.
25.45	Creek, 3 lks. wide, course W.; asc. 145 ft. over S. slope.
40.22	The center E $\frac{1}{16}$ sec. cor. of sec. 5.
	From the center W $\frac{1}{16}$ sec. cor. of sec. 5. N. $0^{\circ} 02' W.$, on the N. and S. centerline of the $NW\frac{1}{4}$ of sec. 5. Descend 120 ft. over NW. slope, through heavy timber and moderate undergrowth.
6.60	McGee Creek, 5 lks. wide, course NE.; asc. 100 ft. over SE. slope.
8.05	Dirt road, 20 lks. wide, bears NE. and SW.
20.04	Point for the NW $\frac{1}{16}$ sec. cor. of sec. 5, at intersection with the E. and W. centerline of the $NW\frac{1}{4}$. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. NW $\frac{1}{16}$ S5 1963 from which A fir, 12 ins. diam., bears N. $41^{\circ} E.$, 29 lks. dist., mkd. NW $\frac{1}{16}$ S5 BT. A fir, 14 ins. diam., bears N. $66^{\circ} W.$, 10 lks. dist., mkd. NW $\frac{1}{16}$ S5 BT.
	Ascend 5 ft. along E. slope.
25.45	Top of ascent, slopes E.; desc. 30 ft. over NE. slope.
31.15	Enter meadow, edge bears E. and W.
32.85	Enter timber, edge bears E. and W.