

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of S. Bdy., T. 21 S., R. 7 W.

CHAINS

$$\begin{array}{r} T\ 21\ S \\ \frac{1}{4}\ S\ 31\ R \\ \frac{1}{4}\ S\ 6\ W \\ T\ 22\ S \\ 1962 \end{array}$$

from which the original bearing trees

A fir, 40 ins. diam., bears N. 49° W., 48 lks. dist., with fragmentary scribe marks visible on scaled bark blaze.

A fir snag, 48 ins. diam., bears S. 37° W., 64 lks. dist., with no marks visible on burned face.

and trees marked by the County Surveyor

A fir, 16 ins. diam., bears N. 75° E., 15½ lks. dist., mkd. $\frac{1}{4}$ S31 CS BT.

A fir, 10 ins. diam., bears South, 48 lks. dist., mkd. $\frac{1}{4}$ S6 CS BT.

Land, mountainous.

Soil, sandy, rocky clay.

Timber, fir, hemlock, cedar, alder, maple, madrone, and chinquapin; undergrowth, vine maple, salmonberry, hazel, arrowwood, huckleberry, salal, poison oak, Ceanothus, blackberry, and fern.

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 21 S., R. 7 W., Willamette Meridian, Oregon

(Restoring the 1884 survey by William P. Wright)

From the cor. of secs. 4, 5, 32, and 33 on the S. bdy. of the Tp.

N. 2° 29' W., bet. secs. 32 and 33, marking and blazing the true line.

Ascend 281 ft. over S. slope through heavy timber and dense undergrowth.

9.75 Spur, slopes S. 65° E.; desc. 150 ft. over NE. slope.

16.50 Creek, 1 lk. wide, course S. 75° E.; asc. 233 ft. over S. slope.

23.65 Spur, slopes S. 65° E.; desc. 75 ft. along E. slope.

29.65 Spur, slopes N. 30° E.; desc. 521 ft. over broken N. slope.

39.77 The $\frac{1}{4}$ sec. cor. of secs. 32 and 33 determined at record bearing and distance from the original bearing trees:

A cedar, 60 ins. diam., bears S. 12° E., 41 lks. dist., with scribe marks BT $\frac{1}{4}$ S visible on partly healed blaze.

A cedar, 53 ins. diam., bears S. 41° W., 13 lks. dist., with scribe marks BT visible on partly healed blaze.

At the corner point