

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 21 S., R. 7 W.

CHAINS

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ S\ 32\ | \ S\ 33 \\ T\ 21\ S\ R\ 7\ W \\ 1964 \end{array}$$

from which new bearing trees

A hemlock, 30 ins. diam., bears N.  $42\frac{1}{2}^\circ$  E., 156 lks. dist., mkd.  $\frac{1}{4}$  S33 BT.

A cedar, 45 ins. diam., bears N.  $89^\circ$  W., 93 lks. dist., mkd.  $\frac{1}{4}$  S32 BT.

N.  $0^\circ 36'$  E., beginning new measurement.

Descend 17 ft. over N. slope.

- 0.30 Little Tom Folley Creek, 15 lks. wide, course E.; asc. 240 ft. over SW. slope.
- 11.55 Spur, slopes W.; desc. 23 ft. over NW. slope.
- 13.75 Ravine, drains S.  $20^\circ$  W.; asc. 496 ft. over SE. slope.
- 29.45 Spur, slopes S.  $15^\circ$  W.; asc. 73 ft. over S. slope.
- 37.35 Top of ascent, slopes W.; desc. 9 ft. along W. slope.
- 37.75 Rock crevice, 20 ft. wide, 20 ft. deep, bears E. and W.
- 38.26 Point for the cor. of secs. 28, 29, 32, and 33, determined at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap marked
- $$\begin{array}{c} T\ 21\ S\ R\ 7\ W \\ S\ 29\ | \ S\ 28 \\ \hline S\ 32\ | \ S\ 33 \\ 1964 \end{array}$$
- from which
- A fir, 8 ins. diam., bears N.  $63^\circ$  E., 69 lks. dist., mkd. T21S R7W S28 BT.
- A fir, 10 ins. diam., bears S.  $86^\circ$  E., 85 lks. dist., mkd. T21S R7W S33 BT.
- A fir, 6 ins. diam., bears S.  $2^\circ$  W., 77 lks. dist., mkd. T21S R7W S32 BT.
- A white fir, 13 ins. diam., bears N.  $12^\circ$  W., 101 lks. dist., mkd. T21S R7W S29 BT.
- Land, mountainous.  
Soil, sandy and rocky clay.  
Timber, fir, hemlock, cedar, maple, alder, and chinquapin; undergrowth, vine maple, salmonberry, hazel, arrowwood, ceanothus, huckleberry, poison oak, reproduction timber, and fern.

From the cor. of secs. 27, 28, 33, and 34; established