

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 21 S., R. 7 W.

CHAINS

by Laban H. Wheeler in 1883; remonumented by W. N. Haines, Registered Surveyor, No. 239, in 1961, with a 1 in. "T" iron, 36 ins. long, driven 24 ins. into decayed stump of original corner tree, from which the remaining original bearing trees:

A fir, 20 ins. diam., bears N. 40° E., 33 lks. dist., with a healed blaze. This tree remarked T21S R7W S27 BT by Haines on a double blaze.

A down and decayed fir, 16 ins. diam., bears S. 30° E., 9 lks. dist., with no marks remaining on opened and decayed blaze.

and trees marked by Haines

A fir, 6 ins. diam., bears S. 13° W., $4\frac{1}{2}$ lks. dist., with scribe marks T21S R7W S33 BT visible on partly healed double blaze.

A fir, 5 ins. diam., bears N. $66\frac{1}{2}^{\circ}$ W., 8 lks. dist., with scribe marks T21S R7W S28 BT visible on partly healed double blaze.

At the corner point

Remove decayed stump of original corner tree down to solid rock, 4 ins. below ground level and set an iron post, 1 in. diam., 14 ins. long, 6 ins. in drill hole in solid rock, with brass cap marked

T 21 S R 7 W
S 28 S 27
S 33 S 34
1964

from which a new bearing tree

A fir, 13 ins. diam., bears S. $26\frac{1}{4}^{\circ}$ E., $43\frac{1}{2}$ lks. dist., mkd. T21S R7W S34 BT.

Deposit the Haines' monument alongside the corner post.

S. $88^{\circ} 56'$ W., bet. secs. 28 and 33.

Ascend 182 ft. over NE. slope, through heavy timber and dense undergrowth.

6.95 Ridge, bears N. 25° W. and S. 25° E.; desc. 205 ft. over SW. slope.

16.30 Bottom of descent, slopes S.; asc. 41 ft. over SE. slope.

23.10 Spur, slopes S.; desc. 397 ft. over general W. slope.

40.305 Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap marked

$\frac{1}{4}$ S 28
S 33
T 21 S R 7 W
1964

from which