

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 21 S., R. 7 W.

CHAINS	
	<p>A white fir, 6 ins. diam., bears N. 54° E., 14 lks. dist., mkd. $\frac{1}{4}$ S28 BT.</p> <p>A hemlock, 7 ins. diam., bears S. 33° E., 51 lks. dist., mkd. $\frac{1}{4}$ S33 BT.</p> <p>Descend 55 ft. over W. slope.</p>
41.60	Creek, 1 lk. wide, course S.; asc. 231 ft. over E. slope.
45.90	Spur, slopes S. 20° E.; asc. 395 ft. along broken S. slope.
60.20	Spur, slopes S. 15° E.; desc. 231 ft. over SW. slope.
67.05	Ravine, drains S.; asc. 126 ft. over SE. slope.
70.45	Spur, slopes S.; desc. 216 ft. over SW. slope.
80.61	The cor. of secs. 28, 29, 32, and 33.
	<p>Land, mountainous. Soil, sandy and rocky clay. Timber, fir, hemlock, cedar, maple, alder, and chinquapin; undergrowth, vine maple, hazel, salmonberry, arrowwood, huckleberry, poison oak, and fern.</p>
	<p>N. 3° 19' E., bet. secs. 28 and 29.</p> <p>Ascend 76 ft. over steep SW. slope, through heavy timber and dense undergrowth.</p>
2.25	Creek, 1 lk. wide, course SW.; asc. 320 ft. over SW. slope.
16.15	Spur, slopes W.; desc. 203 ft. over N. slope.
22.15	Ravine, drains W.; asc. 282 ft. over SW. slope.
37.80	Spur, slopes N. 70° W.; desc. 32 ft. over N. slope.
38.32	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked</p> <p style="text-align: center;"> $\frac{1}{4}$ S 29 S 28 T 21 S R 7 W 1964 </p>
	<p>from which</p> <p>A fir, 12 ins. diam., bears S. $26\frac{1}{4}$° E., 13 lks. dist., mkd. $\frac{1}{4}$ S28 BT.</p> <p>A fir, 10 ins. diam., bears S. 87° W., 19 lks. dist., mkd. $\frac{1}{4}$ S29 BT.</p> <p>Descend 466 ft. over N. slope.</p>
48.15	Little Tom Folley Creek, 2 lks. wide, course N. 60° W.; asc. 419 ft. over SW. slope.
58.00	Ridge, bears NW. and SE.; desc. 134 ft. over general N. slope.