

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 21 S., R. 7 W.

CHAINS

76.64

Point for the cor. of secs. 20, 21, 28, and 29, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

T 21 S R 7 W
 S 20 | S 21
 S 29 | S 28
 1964

from which

A fir, 10 ins. diam., bears N. $16\frac{3}{4}^{\circ}$ E., 11 lks. dist., mkd. T21S R7W S21 BT.

A fir, 8 ins. diam., bears S. $74\frac{1}{4}^{\circ}$ E., 20 lks. dist., mkd. T21S R7W S28 BT.

A fir, 12 ins. diam., bears S. 41° W., 17 lks. dist., mkd. T21S R7W S29 BT.

A fir, 8 ins. diam., bears N. 62° W., $5\frac{1}{2}$ lks. dist., mkd. T21S R7W S20 BT.

Corner falls on spur, slopes NE.

Land, mountainous.

Soil, sandy and rocky clay.

Timber, fir, hemlock, cedar, maple, alder, and chinquapin; undergrowth, vine maple, hazel, salmon-berry, huckleberry, arrowwood, poison oak, and fern.

From the cor. of secs. 21, 22, 27, and 28, established by Laban H. Wheeler in 1883; remonumented by W. N. Haines, Registered Surveyor, No. 239, in 1961, with a 1 in. "T" iron, 36 ins. long, driven 24 ins. in the ground, from which the remaining original bearing trees:

A fir, 70 ins. diam., bears N. 80° E., 53 lks. dist., with a healed blaze.

A fir, 55 ins. diam., bears S. 10° W., 34 lks. dist., with a healed blaze.

A fir, 56 ins. diam., bears N. 52° W., 13 lks. dist., with a healed blaze. This tree remarked BT S21 T21S R7W by Haines on a bark blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

T 21 S R 7 W
 S 21 | S 22
 S 28 | S 27
 1964

from which new bearing trees

A hemlock, 15 ins. diam., bears N. $68\frac{3}{4}^{\circ}$ E., 48 lks. dist., mkd. T21S R7W S22 BT.