

## County Surveyor's Record, Douglas County, Oregon

## Dependent Resurvey, Subdivisional Lines, T. 21 S., R. 7 W.

CHAINS	
4.30	Ravine, drains NE.; asc. 178 ft. over SE. slope.
9.95	Spur, slopes N. 80° E.; desc. 243 ft. over N. slope.
13.00	Ravine, drains NE.; asc. 191 ft. over SE. slope.
19.235	Point for the S 1/16 sec. cor. of secs. 20 and 21. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked  <div style="text-align: center;">           S 1/16            S 20   S 21            1964         </div> from which  A fir, 12 ins. diam., bears N. 7½° E., 16½ lks. dist., mkd. S 1/16 S21 BT.  A fir, 15 ins. diam., bears N. 35° W., 44½ lks. dist., mkd. S 1/16 S20 BT.  Ascend 87 ft. over SE. slope.
27.35	Spur, slopes S. 80° E.; desc. 78 ft. along broken E. slope.
32.75	Spur ridge, bears N. 15° E. and S. 15° W.; desc. 103 ft. over NW. slope.
38.47	Point for the ¼ sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked  <div style="text-align: center;"> <math>\frac{1}{4}</math>            S 20   S 21            T 21   S R 7 W            1964         </div> from which  A fir, 26 ins. diam., bears S. 25° E., 35½ lks. dist., mkd. ¼ S21 BT.  A fir, 16 ins. diam., bears S. 61° W., 27½ lks. dist., mkd. ¼ S20 BT.  Descend 10 ft. over NW. slope.
39.00	Ravine, drains N. 65° W.; asc. 20 ft. over gentle SW. slope.
44.20	Spur, slopes N. 55° W.; desc. 513 ft. over general N. slope.
56.55	Halfway Creek, 20 lks. wide, course N. 75° W.; asc. 6 ft. over creek bank.
57.705	Point for the N 1/16 sec. cor. of secs. 20 and 21. Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap marked  <div style="text-align: center;">           N 1/16            S 20   S 21            1964         </div> from which