

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 21 S., R. 7 W.

CHAINS

A fir, 15 ins. diam., bears N. $67\frac{1}{2}^{\circ}$ E., 105 lks. dist., mkd. N 1/16 S21 BT.

A hemlock, 15 ins. diam., bears S. 3° W., 73 lks. dist., mkd. N 1/16 S20 BT.

Descend 2 ft. over N. slope.

57.80 Creek, 5 lks. wide, course S. 20° W.; asc. 342 ft. over general S. slope.

76.94 The cor. of secs. 16, 17, 20, and 21, determined from the original bearing trees:

A cedar, 42 ins. diam., bears N. 61° E., 68 lks. dist., with scribe marks T21S R7W visible on opened blaze. (Record calls this tree a fir.)

A decayed fir stump, 20 ins. diam., bears S. 60° E., 78 lks. dist., with no marks remaining.

A fir, 60 ins. diam., bears S. 22° W., 65 lks. dist., with scribe marks BT S visible on scaled bark blaze.

A fir, 55 ins. diam., bears N. 47° W., 95 lks. dist., with fragmentary scribe marks visible on badly scaled bark blaze. (Record distance, 90 lks.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

T 21 S	R 7 W
S 17	S 16
S 20	S 21
1964	

from which new bearing trees

A fir, 13 ins. diam., bears N. $79\frac{1}{4}^{\circ}$ E., $20\frac{1}{2}$ lks. dist., mkd. T21S R7W S16 BT.

A fir, 15 ins. diam., bears S. $47\frac{1}{4}^{\circ}$ E., 43 lks. dist., mkd. T21S R7W S21 BT.

A fir, 22 ins. diam., bears S. $86\frac{1}{2}^{\circ}$ W., $69\frac{1}{2}$ lks. dist., mkd. T21S R7W S20 BT.

A fir, 17 ins. diam., bears N. 53° W., 29 lks. dist., mkd. T21S R7W S17 BT.

Land, mountainous.

Soil, sandy and rocky clay.

Timber, fir, hemlock, cedar, maple, alder, and chinquapin; undergrowth, vine maple, salmonberry, hazel, huckleberry, salal, ceanothus, poison oak, and fern.

From the cor. of secs. 5, 6, 31, and 32 on the S. bdy. of the Tp.

N. $2^{\circ} 36'$ W., bet. secs. 31 and 32.

Descend 91 ft. along broken W. slope, through heavy timber and dense undergrowth.