

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 21 S., R. 7 W.

CHAINS

- 21.05 Little Paradise Creek, 8 lks. wide, course S. 20° W.; asc. 147 ft. over SE. slope.
- 23.10 Spur, slopes S. 70° E.; desc. 30 ft. over NE. slope.
- 24.10 Ravine, drains S. 65° E.; asc. 179 ft. over SE. slope.
- 32.20 Spur, slopes E.; desc. 99 ft. over NE. slope.
- 34.10 Creek, 2 lks. wide, course S. 65° E.; asc. 54 ft. over SE. slope.

40.81 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

$\frac{1}{4}$
 S 31 | S 32
 T 21 S R 7 W
 1964

from which

A cedar, 17 ins. diam., bears N. 21° E., 33 lks. dist., mkd. $\frac{1}{4}$ S32 BT.

A cedar, 10 ins. diam., bears N. $24\frac{1}{4}$ ° W., $15\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S31 BT.

Ascend 105 ft. over broken SE. slope.

- 44.80 Spur, slopes E.; desc. 82 ft. over NE. slope.
- 47.20 Ravine, drains S. 55° E.; asc. 183 ft. over broken SE. slope.
- 50.95 Spur, slopes S. 30° E.; desc. 63 ft. over NE. slope.
- 55.55 Creek, 1 lk. wide, course S. 60° E.; asc. 466 ft. over SE. slope.
- 75.75 Ridge, bears N. 40° E. and S. 40° W.; desc. 26 ft. over NW. slope.
- 81.62 The cor. of secs. 29, 30, 31, and 32, determined at record bearing and distance from the remaining original bearing trees:
- A fir, 38 ins. diam., bears N. 27° E., 58 lks. dist., with no marks remaining on scaled bark blaze.
- A fir, 54 ins. diam., bears N. 14° W., 64 lks. dist., with fragmentary scribe marks visible on badly scaled bark blaze.
- At the corner point
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

T 21 S R 7 W
 S 30 | S 29
 S 31 | S 32
 1964