

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 21 S., R. 7 W.

CHAINS

from which new bearing trees

A fir, 10 ins. diam., bears N. 35° E., 10 lks. dist., mkd. T21S R7W S29 BT.

A fir, 16 ins. diam., bears S. 53° E., 33 lks. dist., mkd. T21S R7W S32 BT.

A fir, 5 ins. diam., bears S. 27° W., 14½ lks. dist., mkd. T21S R7W S31 BT.

A fir, 5 ins. diam., bears N. 21° W., 56 lks. dist., mkd. T21S R7W S30 BT.

Land, mountainous.

Soil, sandy and rocky clay.

Timber, fir, hemlock, cedar, maple, alder, and chinquapin; undergrowth, vine maple, salmonberry, hazel, huckleberry, arrowwood, poison oak, salal, Oregon grape, and fern.

From the cor. of secs. 28, 29, 32, and 33.

N. 85° 16' W., bet. secs. 29 and 32.

Descend 201 ft. over W. slope changing to SW. slope, through heavy timber and dense undergrowth.

7.40 Ravine, drains S.; asc. 156 ft. over SE. slope.

13.65 Spur, slopes S. 30° W.; desc. 515 ft. over SW. slope, changing to W. slope.

38.40 Little Tom Folley Creek, 8 lks. wide, course S. 20° W.; asc. 79 ft. over E. slope.

40.27 The ¼ sec. cor. of secs. 29 and 32, determined at intersection of the facing of an original bearing tree and Wright's line from the west as indicated by a bark blaze on a burned fir snag about 6 chs. westerly from the corner. This position is substantiated by the position of the creek shown in Wright's notes as being 2.08 chs. east of the ¼ sec. corner and by the record distance of the W ½ mile of this line. The bearing trees shown in the original field notes are actually those for the ¼ sec. cor. of secs. 32 and 33, which still exist at that corner. The bearing tree south of the corner cannot be identified and may have been carried down hill in a slide. From the established corner point, the original bearing tree:

A fir, 67 ins. diam., bears N. 35° W., 24 lks. dist., with scribe marks BT ¼ S visible on bark blaze. These marks are identical in style, size, and character to those found on other bearing trees marked by Wright in this area.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap marked

$$\frac{1}{4} \begin{array}{l} S 29 \\ S 32 \end{array}$$

T 21 S R 7 W
1964