

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 21 S., R. 7 W.

CHAINS

37.60

Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31 at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

$\frac{1}{4} \frac{S\ 30}{S\ 31}$
T 21 S R 7 W
1964

from which

A white fir, 20 ins. diam., bears N. $53\frac{1}{2}^\circ$ W., $64\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S30 BT.

A cedar, 72 ins. diam., bears S. 63° E., 66 lks. dist., mkd. $\frac{1}{4}$ S31 BT.

Descend 77 ft. over SW. slope.

46.25

Ravine, drains S.; asc. 56 ft. over SE. slope.

49.20

Ridge, bears NE. and SW.; desc. 132 ft. over NW. slope.

55.80

Ravine, drains N.; asc. 5 ft. along N. slope.

56.40

Point for the W $\frac{1}{16}$ sec. cor. of secs. 30 and 31.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

W $\frac{1}{16} \frac{S\ 30}{S\ 31}$
1964

from which

A hemlock, 13 ins. diam., bears N. 43° W., 44 lks. dist., mkd. W $\frac{1}{16}$ S30 BT.

A hemlock, 5 ins. diam., bears S. $10\frac{1}{2}^\circ$ E., 22 lks. dist., mkd. W $\frac{1}{16}$ S31 BT.

Ascend 39 ft. over NE. slope.

58.30

Spur, slopes N. 20° W.; desc. 361 ft. over NW. slope.

68.05

Creek, 3 lks. wide, course N. 35° W.; asc. 174 ft. over NE. slope.

72.85

The cor. of secs. 25, 30, 31, and 36 on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap marked and witnessed as described in the official record of the 1952 resurvey.

Land, mountainous.
Soil, sandy and rocky clay.
Timber, fir, hemlock, cedar, maple, alder, and chinquapin; undergrowth, vine maple, salmonberry, hazel, huckleberry, salal, arrowwood, poison oak, and fern.

Fl. O.K. by
L. ROBERTS
5-30-82
M 90-21