

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 21 S., R. 7 W.

CHAINS

From the cor. of secs. 29, 30, 31, and 32.

N. $1^{\circ}13'$ W., bet. secs. 29 and 30.

Descend 71 ft. over NW. slope, through heavy timber and dense undergrowth.

4.50 Bottom of descent, slopes W.; asc. 57 ft. over SW. slope.

11.35 Spur, slopes N. 5° E.; desc. 278 ft. over broken NW. slope.18.79 Point for the S $\frac{1}{16}$ sec. cor. of secs. 29 and 30.

Set an iron post, 16 ins. long, 1 in. diam., 8 ins. in drill hole in solid rock, with brass cap marked

$$\begin{array}{c} \text{S } \frac{1}{16} \\ \text{S } 30 | \text{S } 29 \\ 1964 \end{array}$$

from which

A fir, 10 ins. diam., bears S. $80\frac{1}{4}^{\circ}$ E., 55 lks. dist., mkd. S $\frac{1}{16}$ S29 BT.A hemlock, 12 ins. diam., bears S. 28° W., 66 lks. dist., mkd. S $\frac{1}{16}$ S30 BT.

Descend 325 ft. over broken N. slope.

30.30 Creek, 1 lk. wide, course N. 30° W.; asc. 21 ft. over SW. slope.

36.05 Top of ascent, slopes W.; desc. 69 ft. over NW. slope.

37.35 Creek, 1 lk. wide, course S. 60° W.; asc. 10 ft. over SW. slope.37.58 Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked
$$\begin{array}{c} \frac{1}{4} \\ \text{S } 30 | \text{S } 29 \\ \text{T } 21 \text{ S } \text{ R } 7 \text{ W} \\ 1964 \end{array}$$

from which

A fir, 22 ins. diam., bears N. $68\frac{1}{4}^{\circ}$ E., 33 lks. dist., mkd. $\frac{1}{4}$ S29 BT.A fir, 22 ins. diam., bears S. $9\frac{1}{2}^{\circ}$ W., 110 lks. dist., mkd. $\frac{1}{4}$ S30 BT.

Ascend 166 ft. over broken SW. slope.

48.20 Spur, slopes N. 85° W.; desc. 206 ft. over NW. slope.

52.20 Creek, 5 lks. wide, course W.; asc. 80 ft. over SW. slope.

56.37 Point for the N $\frac{1}{16}$ sec. cor. of secs. 29 and 30.

Fd. O.K. by
L. ROBERTS
5-30-82
M 90-21