

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 21 S., R. 7 W.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

N 1/16
S 30 | S 29
T 21 S R 7 W
1964

from which

A fir, 9 ins. diam., bears S. 68° E., 15 lks. dist., mkd. N 1/16 S29 BT.

A fir, 9 ins. diam., bears N. 18° W., 17 lks. dist., mkd. N 1/16 S30 BT.

Ascend 255 ft. over SW. slope.

70.40 Spur, slopes N. 85° W.; desc. 292 ft. over NW. slope.

75.16 The cor. of secs. 19, 20, 29, and 30, determined from the original bearing trees:

A burned and decayed fir stump, 15 ins. diam., bears N. 50° E., 67 lks. dist., with no marks remaining. (Record distance, 77 lks.)

A burned and decayed fir snag, 50 ins. diam., bears S. 3° E., 30 lks. dist., with no marks remaining.

A decayed fir snag, 45 ins. diam., bears S. 40° W., 56 lks. dist., with scribe marks S30 T21S R7W BT visible on bark blaze.

A burned and decayed fir stump, 20 ins. diam., bears N. 13° W., 130 lks. dist., with no marks remaining.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

T 21 S R 7 W
S 19 | S 20
S 30 | S 29
1964

from which new bearing trees

A fir, 36 ins. diam., bears N. 5° E., $61\frac{1}{2}$ lks. dist., mkd. T21S R7W S20 BT.

A fir, 7 ins. diam., bears S. 54° E., $61\frac{1}{2}$ lks. dist., mkd. T21S R7W S29 BT.

A fir, 28 ins. diam., bears S. 53° W., 107 lks. dist., mkd. T21S R7W S30 BT.

A fir, 10 ins. diam., bears N. 15° W., 108 lks. dist., mkd. T21S R7W S19 BT.

Land, mountainous.

Soil, sandy and rocky clay.

Timber, fir, hemlock, cedar, maple, alder, and chinquapin; undergrowth, vine maple, salmonberry, salal, hazel, huckleberry, arrowwood, Oregon grape, poison oak, and fern.