

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 21 S., R. 7 W.

CHAINS

From the cor. of secs. 20, 21, 28, and 29.

N. 87° 40' W., bet. secs. 20 and 29.

Descend 90 ft. over NW. slope, through heavy timber and dense undergrowth.

4.40 Ravine, drains N. 30° E.; asc. 183 ft. over E. slope.

7.60 Spur, slopes N. 10° E.; desc. 318 ft. over broken NW. slope.

13.95 Ravine, drains NW.; asc. 216 ft. over NE. slope.

19.16 Point for the E 1/16 sec. cor. of secs. 20 and 29.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

$$E \frac{1}{16} \frac{S \ 20}{S \ 29}$$

1964

from which

A fir, 9 ins. diam., bears N. 12¾° W., 6 lks. dist., mkd. E 1/16 S20 BT.

A fir, 11 ins. diam., bears S. 7¼° E., 36 lks. dist., mkd. E 1/16 S29 BT.

Ascend 60 ft. over NE. slope.

24.95 Ridge, bears N. 10° E. and S. 10° W.; desc. 306 ft. over broken NW. slope.

37.15 Bottom of descent, slopes N.; asc. 47 ft. over NE. slope.

37.75 Spur, slopes N. 20° W.; desc. 20 ft. over W. slope.

38.32 The ¼ sec. cor. of secs. 20 and 29, determined at record bearing and distance from the original bearing trees; there is no evidence of the corner tree.

A fir, 30 ins. diam., bears N. 30° E., 11 lks. dist., with fragmentary scribe marks visible on scaled bark blaze.

A down fir, 30 ins. diam., bears S. 5° E., 32 lks. dist., with no marks remaining.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

$$\frac{1}{4} \frac{S \ 20}{S \ 29}$$

T 21 S R 7 W
1964

from which new bearing trees

A fir, 16 ins. diam., bears N. 44¼° E., 75 lks. dist., mkd. ¼ S20 BT.