

County Surveyor's Record, Douglas County, Oregon

T. 23 S., R. 8 W.

CHAINS

The history of surveys of that portion of township 23 south, range 8 west, Willamette Meridian, Oregon, covered by this resurvey, is as follows:

The east boundary of the township was surveyed by Thomas H. Hutchinson, under joint contract with Ambrose N. Armstrong in 1857. A portion of the subdivisional lines, including those bounding section 25, were surveyed by Dennis Hathorn, in 1857. The survey of the township was completed by Williams R. Whipple, in 1894. Whipple retraced a part of the lines surveyed by Hathorn, including the line between sections 24 and 25.

The resurvey was made at the request of the Coos Bay District Manager for administrative purposes of the Bureau of Land Management.

Preliminary to the resurvey the lines of the original surveys are retraced and search is made for all corners and other calls of the record. Identified corners are remonumented in their original positions, lost corners are reestablished and remonumented at proportionate positions based on the official record. The retracement data are thoroughly verified and only the true line field notes are given herein. Only lines bounding or crossing public lands are blazed.

The resurvey was executed in accordance with the specifications set forth in the Manual of Surveying, Instructions, 1947, and Special Instructions dated February 12, 1964, and May 3, 1957.

The directions of lines were determined by the solar compass method.

The geographic position of the corner of sections 25, 30, 31, and 36, computed from a tie made to United States Coast and Geodetic Survey triangulation station KELLOGG, 1953, is as follows:

Latitude 43° 32' 02.3" N. Longitude 123° 34' 59.2" W.

The mean magnetic declination is 19° 56' E.

Dependent Resurvey of a Portion of the East Boundary T. 23 S., R. 8 W., Willamette Meridian, Oregon

(Restoring the 1857 survey by Thomas H. Hutchinson and Ambrose N. Armstrong.)

The cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., remonumented by James W. Byron, Deputy County Surveyor, in 1957, with an iron post, 1 in. diam., firmly set, protruding 10 ins. above ground, with brass cap marked

COUNTY SURVEYORS OFFICE

R T 23 S R
 8 S 25 | S 30 7
 W S 36 | S 31 W
 1957

from which the original bearing trees

Fd by:
Dew BENTZ
3/02
M 90-38A+B