

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. Bdy., T. 23 S., R. 8 W.

CHAINS

A fir, 35 ins. diam., bears N. 4° E., 158 lks. dist., with no marks visible on opened and rotted blaze.

A fir stump, 26 ins. diam., bears S. 50° W., 130 lks. dist., with a healed blaze.

A sawed fir stump, 32 ins. diam., bears N. 67° W., 98 lks. dist., with fragmentary scribe marks visible on opened blaze.

and trees marked by James W. Byron in 1957

A fir, 11 ins. diam., bears N. 43 $\frac{3}{4}$ ° E., 20 lks. dist., with healed double blaze.

A fir, 8 ins. diam., bears S. 47° E., 25 lks. dist., with healed double blaze.

A fir, 9 ins. diam., bears S. 28 $\frac{3}{4}$ ° W., 13 $\frac{1}{2}$ lks. dist., with healed double blaze.

A fir, 9 ins. diam., bears N. 67° W., 17 lks. dist., with healed double blaze.

N. 0° 07' E., bet. secs. 25 and 30, marking and blazing the true line.

Ascend 30 ft. over SW. slope, through scattering timber and light undergrowth.

- 1.30 Spur, slopes S. 80° W.; desc. 90 ft. over NW. slope.
- 6.30 Creek, 2 lks. wide, course S. 75° W.; asc. 330 ft. over SE. slope.
- 34.10 Trail, 10 lks. wide, bears NW. and SE.
- 37.00 Spur, slopes SE.; desc. 15 ft. over NE. slope.
- 40.01 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

$\frac{1}{4}$
 S 25 | S 30
 R 8 W | R 7 W
 T 23 S
 1964

Fd by:
DON BENTZ
3/83
M 90-38 A $\frac{1}{4}$ B

from which

A fir, 28 ins. diam., bears N. 9° E., 23 lks. dist., marked $\frac{1}{4}$ S30 BT.

A fir, 23 ins. diam., bears S. 69 $\frac{1}{2}$ ° W., 106 lks. dist., marked $\frac{1}{4}$ S25 BT.

Descend 90 ft. over NE. slope.

- 49.40 Ravine, drains E.; asc. 160 ft. over SE. slope.
- 60.015 Point for the N 1/16 sec. cor. of secs. 25 and 30.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked