

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. Bdy., T. 23 S., R. 8 W.

CHAINS

N 1/16
S 25 | S 30
1964

from which

An oak, 20 ins. diam., bears N. 45° E., 101 lks. dist., mkd. N 1/16 S30 BT.

A fir, 30 ins. diam., bears N. 62° W., 121 lks. dist., mkd. N 1/16 S25 BT.

Ascend 280 ft. over SE. slope.

69.50 Ridge, bears N. 70° E. and S. 70° W., leave timber, enter open pasture, edge bears same as ridge; desc. 140 ft. over N. slope.

80.02 Point for the cor. of secs. 19, 24, 25, and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap marked

T 23 S
R 8 W R 7 W
S 24 | S 19
S 25 | S 30
1964

*Fr. by:
Don BENTZ
3/83
M 90-38 A & B*

from which

A fir, 18 ins. diam., bears N. 6° E., 406 lks. dist., mkd. T23S R7W S19 BT.

A fir, 37 ins. diam., bears N. 39° W., 571 lks. dist., mkd. T23S R8W S24 BT.

No suitable bearing trees available within limits in secs. 25 and 30.

Set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.

From this point United States Coast and Geodetic Survey triangulation station KELLOGG, 1953, bears S. 11° 48' E., 8.91 chs. dist., monumented with a standard 3 in. brass cap set in an iron post, 3 ins. diam., projecting 4 ins. above ground.

Land, mountainous.
Soil, sandy clay loam.
Timber, fir, hemlock, cedar, maple, and madrone; undergrowth, vine maple, hazel, arrowwood, salmonberry, poison oak, Oregon grape, salal, and fern.

N. 0° 07' E., bet. secs. 19 and 24.

Descend 270 ft. over broken NE. slope, across open pasture.

3.60 Dirt road, 10 lks. wide, bears E. and W.; enter scattering timber and dense undergrowth, edge bears same as road.

20.005 Point for the S 1/16 sec. cor. of secs. 19 and 24.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap marked