

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. Bdy., T. 23 S., R. 8 W.

CHAINS

S 1/16  
S 24|S 19  
1964

from which

A maple, 16 ins. diam., bears S.  $44\frac{1}{2}^{\circ}$  E., 48 lks.  
dist., mkd. S 1/16 S19 BT.

A cedar, 24 ins. diam., bears S.  $80\frac{1}{2}^{\circ}$  W., 58 lks.  
dist., mkd. S 1/16 S24 BT.

Descend 15 ft. over NE. slope.

20.50 Creek, 2 lks. wide, course E.; asc. 50 ft. over SE.  
slope.

36.00 Spur, slopes N.  $35^{\circ}$  E.; desc. 50 ft. over NW. slope.

40.01 The  $\frac{1}{4}$  sec. cor. of secs. 19 and 24, remonumented by  
James W. Byron, Deputy County Surveyor, in 1960, with  
an iron post, 1 in. diam., firmly set, protruding  
16 ins. above the ground, with brass cap marked

## COUNTY SURVEYORS OFFICE

T 23 S  
R S 24|S 19 R  
8  $\frac{1}{4}$  COR 7  
W 1960 W

from which the original bearing trees

A fir, 37 ins. diam., bears N.  $3^{\circ}$  E., 36 lks.  
dist., with a healed blaze.

A sawed fir stump, 28 ins. diam., bears N.  $70^{\circ}$  W.  
26 lks. dist., with fragmentary scribe marks  
visible on opened blaze.

and a tree marked by J. W. Byron, in 1960

A fir, 13 ins. diam., bears S.  $80^{\circ}$  W., 80 lks.  
dist., with healed double blaze.

---

N.  $0^{\circ} 29'$  E., beginning new measurement

Descend 280 ft. over NE. slope.

10.20 Ravine, drains N.  $30^{\circ}$  W.; asc. 10 ft. over SW. slope.

20.49 Point for the N 1/16 sec. cor. of secs. 19 and 24.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins.  
in the ground, with brass cap marked

N 1/16  
S 24|S 19  
1964

from which

A fir, 23 ins. diam., bears S.  $86\frac{1}{2}^{\circ}$  E.,  $72\frac{1}{2}$  lks.  
dist., mkd. N 1/16 S19 BT.

A fir, 13 ins. diam., bears S.  $34^{\circ}$  W., 56 lks.  
dist., mkd. N 1/16 S24 BT.