

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. Bdy., T. 23 S., R. 8 W.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

$\frac{1}{4}$
S 13 | S 18
T 23 S
R 8 W R 7 W
1964

from which

A white fir, 15 ins. diam., bears S. 76° E., 35 lks. dist., mkd. $\frac{1}{4}$ S18 BT.

A cedar, 13 ins. diam., bears S. 35° W., 47 lks. dist., mkd. $\frac{1}{4}$ S13 BT.

Descend 108 ft. over NE. slope.

45.20 Mehl Creek, 30 lks. wide, course NW.; asc. 20 ft. over SW. slope.

52.00 Creek, 1 lk. wide, course W.; asc. 10 ft. over SW. slope.

58.98 Point for the N $\frac{1}{16}$ sec. cor. of secs. 13 and 18. The corner point falls in Mehl Creek road, 35 lks. wide, bears N. 50° W. and S. 50° E.

Set a steel bridge spike, $\frac{1}{4}$ in. diam., 10 ins. long, the top 4 ins. below the surface of the road.

from which bearing trees and a reference monument

A fir, 18 ins. diam., bears N. 10° E., 79 lks. dist., mkd. N $\frac{1}{16}$ S18 BT.

A white fir, 16 ins. diam., bears S. $20\frac{1}{2}^\circ$ W., 167 lks. dist., mkd. N $\frac{1}{16}$ S13 BT.

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 38° E., 65 lks. dist., with brass cap mkd. N $\frac{1}{16}$ S18 RM 1964 and an arrow pointing to the corner.

Ascend 330 ft. over SW. slope.

78.64 The cor. of secs. 7, 12, 13, and 18, determined at record bearing and distance from the remaining original bearing trees:

A stump hole, bears N. 5° E., 31 lks. dist.

A sawed fir stump, 38 ins. diam., bears S. 60° E. 30 lks. dist., with faint axe marks visible on opened blaze.

A rotted fir stump, size indeterminate, bears N. 20° W., 17 lks. dist., with no marks visible.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked