

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. Bdy., T. 23 S., R. 8 W.

CHAINS

T 23 S
R 8 W R 7 W
S 12 | S 7
S 13 | S 18
1964

from which new bearing trees

A fir, 3 ins. diam., bears N. 23° E., 47 lks. dist., mkd. T23S R7W S7 BT.

A fir, 8 ins. diam., bears S. 82½° E., 86 lks. dist., mkd. T23S R7W S18 BT.

A fir, 15 ins. diam., bears S. 28° W., 286 lks. dist., mkd. T23S R8W S13 BT.

A white fir, 6 ins. diam., bears N. 73½° W., 79 lks. dist., mkd. T23S R8W S12 BT.

Land, mountainous.

Soil, sandy clay loam.

Timber, fir, hemlock, cedar, oak, maple, alder, and madrone; undergrowth, vine maple, arrowwood, hazel, poison oak, salmonberry, huckleberry, ceanothus, Oregon grape, salal, and fern.

Dependent Resurvey of a Portion
of the Subdivisional Lines,
T. 23 S., R. 8 W., Willamette Meridian, Oregon

(Restoring the 1857 survey by Dennis Hathorn and the
1894 retracement by Williams R. Whipple)

From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp.

S. 89° 55' W., bet. secs. 25 and 36.

Descend 80 ft. over SW. slope, through scattering timber and dense undergrowth, marking and blazing the true line.

- 4.80 Confluence of two small creeks from NE. and NW., 3 lks. wide, course S.; asc. 170 ft. over E. slope.
- 13.20 Spur, slopes S. 60° E.; desc. 30 ft. over SW. slope.
- 16.50 Ravine, drains S. 60° E.; asc. 110 ft. over E. slope.
- 17.50 Abandon dirt road, 15 lks. wide, bears N. 60° W. and S. 60° E.
- 24.80 Spur, slopes S.; desc. 330 ft. over SW. slope.
- 36.60 Creek, 10 lks. wide, course S. 35° E.; asc. 120 ft. over E. slope.
- 40.18 The $\frac{1}{4}$ sec. cor. of secs. 25 and 36, monumented with an iron pipe, 18 ins. long, $\frac{1}{2}$ in. diam., firmly set 10 ins. in the ground, from which the original bearing tree
- A down fir, 24 ins. diam., bears N. 50° W., 25 lks. dist., with axe marks visible on opened and rotted blaze.