

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 23 S., R. 8 W.

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked
$$\frac{1}{4} \frac{S \ 25}{S \ 36}$$

T 23 S R 8 W
1964

from which new bearing trees

A cedar, 14 ins. diam., bears N. 27° W., 93 lks. dist., mkd. $\frac{1}{4}$ S25 BT.A hemlock, 8 ins. diam., bears S. $14\frac{1}{2}^\circ$ E., 38 lks. dist., mkd. $\frac{1}{4}$ S36 BT.

Reset the iron pipe alongside the iron post.

S. $89^\circ 47'$ W., beginning new measurement.

Ascend 100 ft. over NE. slope.

2.50 Spur, slopes N.; desc. 70 ft. over NW. slope.

4.90 Ravine, drains N.; asc. 220 ft. over NE. slope.

19.94 Point for the W $1/16$ sec. cor. of secs. 25 and 36.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked
$$W \ 1/16 \ \frac{S \ 25}{S \ 36}$$

1964

from which

A fir, 22 ins. diam., bears N. $67\frac{1}{2}^\circ$ W., 68 lks. dist., mkd. W $1/16$ S25 BT.A fir, 22 ins. diam., bears S. $51\frac{1}{2}^\circ$ W., 70 lks. dist., mkd. W $1/16$ S36 BT.

Ascend 60 ft. along N. slope.

39.88 The cor. of secs. 25, 26, 35, and 36, determined at record bearing and distance from the remaining original bearing trees:

A down fir, 18 ins. diam., bears S. 5° E., 11 lks. dist., with a healed blaze.A maple, 25 ins. diam., bears S. 72° W., 64 lks. dist., with no marks visible on opened and rotted blaze. (Whipple, 1894)A sawed fir stump, 25 ins. diam., bears N. 30° W., 22 lks. dist., with no marks visible.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked