

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 23 S., R. 8 W.

CHAINS

A down fir, 16 ins. diam., bears N. 10° W., 60 lks. dist., with no marks visible.

and trees marked by J. W. Byron, in 1960

A fir, 65 ins. diam., bears S. 71° W., 70 lks. dist., with a healed blaze.

A fir, 22 ins. diam., bears N. 41½° W., 85 lks. dist., with a healed blaze.

Land, mountainous.

Soil, sandy clay loam.

Timber, fir, hemlock, cedar, maple, madrone, oak, alder, dogwood, and willow; undergrowth, vine maple, hazel, salmonberry, huckleberry, ceanothus, arrowwood, blackberry, poison oak, Oregon grape, salal, and fern.

From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp.

S. 89° 39' W., bet. secs. 24 and 25.

Ascend 10 ft. over NE. slope, across open pasture.

8.30 Ridge, bears N. and S., enter light timber and dense undergrowth, edge bears same as ridge; desc. 400 ft. over NW. slope.

20.355 Point for the E 1/16 sec. cor. of secs. 24 and 25.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

$$E \frac{1}{16} \frac{S \ 24}{S \ 25}$$

1964

from which

A fir, 28 ins. diam., bears N. 75° E., 27 lks. dist., mkd. E 1/16 S24 BT.

A fir, 31 ins. diam., bears S. 8° W., 30 lks. dist., mkd. E 1/16 S25 BT.

Descend 20 ft. over NW. slope.

22.80 Creek, 1 lk. wide, course N. 5° E.; asc. 380 ft. over NE. slope.

35.60 Spur, slopes N. 30° W.; desc. 160 ft. over W. slope.

40.71 Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, to solid rock, with brass cap marked

$$\frac{1}{4} \frac{S \ 24}{S \ 25}$$

T 23 S R 8 W  
1964