

County Surveyor's Record, Douglas County, Oregon

T. 28 S., R. 8 W.

CHAINS

The history of surveys in that portion of township 28 south, range 8 west, Willamette Meridian, Oregon, covered by this resurvey is as follows:

The south and west boundaries and a portion of the subdivisional lines were surveyed by Dennis Hathorn in 1855. The south 2 miles of the west boundary were dependently resurveyed by William W. Glenn in 1959.

The resurvey was made at the request of the Roseburg District Manager for administrative purposes of the Bureau of Land Management.

Preliminary to the resurvey the lines of the original survey are retraced and search is made for all corners and other calls of the record. Identified corners are remonumented in their original positions, lost corners are reestablished and remonumented at proportionate positions based on the original record. The retracement data are thoroughly verified and only the true line field notes are given herein. Only lines bounding or crossing public lands are blazed.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and Special Instructions dated June 19, 1964, under Group No. 552, Oregon.

The directions of the lines were determined by the solar transit method.

The geographic position of the corner of sections 5, 6, 31, and 32 on the south boundary of the township as scaled from the Camas Valley Quadrangle Map, prepared by the United States Geological Survey, in 1955, is as follows:

Latitude $43^{\circ} 05.1' N.$ Longitude $123^{\circ} 40.9' W.$

The mean magnetic declination is $19^{\circ} 15' E.$

Dependent Resurvey of a Portion of the South Boundary,
T. 28 S., R. 8 W., Willamette Meridian, Oregon

(Restoring the 1855 survey by Dennis Hathorn)

The cor. of secs. 5, 6, 31, and 32 on the S. bdy. of the Tp., recorded and remonumented by J. W. Byron, Deputy County Surveyor, in 1957, with an iron pipe, 1 in. diam., 12 ins. above the ground, firmly set, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 28 S		
S 31	S 32	R
S 6	S 5	8
T 29 S		W
1957		

from which the remaining original bearing trees

A sawed fir stump, 28 ins. diam., bears $N. 32^{\circ} E.$, 21 lks. dist., with fragmentary scribe marks visible on opened blaze.