

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of S. Bdy., T. 28 S., R. 8 W.

CHAINS

A fir, 8 ins. diam., bears S. $6\frac{1}{2}^{\circ}$ W., $34\frac{1}{2}$ lks. dist., with fragmentary scribe marks visible on partially healed blaze.

and a bearing tree marked by William W. Glenn, Cadastral Surveyor, in 1959

A fir, 8 ins. diam., bears S. $43\frac{1}{2}^{\circ}$ E., 56 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

from which a new bearing tree

A white fir, 12 ins. diam., bears N. 73° W., 248 lks. dist., mkd. T28S R9W S36 BT.

Land, gently rolling.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, oak, maple, alder, ash, dogwood, yew, madrone, chinquapin, and cascara; undergrowth, vine maple, hazel, manzanita, ocean spray, elderberry, blackberry, huckleberry, rhododendron, Oregon grape, fern, and salal.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 28 S., R. 8 W., Willamette Meridian, Oregon

(Restoring the 1855 survey by Dennis Hathorn)

From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp.

N. $0^{\circ} 05'$ W., bet. secs. 31 and 32, marking and blazing the true line.

Descend 105 ft. over NW. slope, across logged area, through heavy young timber and dense undergrowth.

16.96 Creek, 1 lk. wide, course W.; desc. 5 ft. over NW. slope.

20.15 Point for the S $1/16$ sec. cor. of secs. 31 and 32.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S $1/16$
S 31 | S 32
1964

from which

A white fir, 9 ins. diam., bears S. 49° E., 102 lks. dist., mkd. S $1/16$ S32 BT.

A white fir, 8 ins. diam., bears S. $23\frac{1}{2}^{\circ}$ W., 54 lks. dist., mkd. S $1/16$ S31 BT.

Descend 50 ft. over NW. slope.

21.50 Dirt road, 15 lks. wide, bears E. and W.

29.13 Creek, 2 lks. wide, course S. 80° W.; desc. 15 ft. over N. slope.

35.90 Leave timber; enter pasture land, edge bears generally E. and W.