

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 28 S., R. 8 W.

CHAINS	
39.40	Middle Fork of Coquille River, 6 lks. wide, course W.; asc. 5 ft. over general S. slope.
40.30	Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 28 S R 8 W S 31   S 32 1964
	from which
	A fir, 16 ins. diam., bears N. $77^{\circ}$ E., 161 lks. dist., mkd. $\frac{1}{4}$ S32 BT.
	A cedar, 7 ins. diam., bears S. $81^{\circ}$ W., $78\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S31 BT.
	From this point an iron pipe, $1\frac{1}{2}$ ins. diam., 5 ins. above ground, firmly set, and in a barbed wire fence which bears N. and S., bears S. $26^{\circ}$ E., 0.125 chs. dist.
	Ascend 2 ft. over S. slope.
42.68	Estes Creek, 6 lks. wide, course W.; asc. 10 ft. over S. slope.
46.75	Same creek, from NE., course SE.; asc. 5 ft. over S. slope.
49.50	Same creek, course E.; asc. 50 ft. over SW. slope.
55.35	Upper Camas Road, asphaltic, 20 lks. wide, bears NE. and SW.
60.45	Point for the N $\frac{1}{16}$ sec. cor. of secs. 31 and 32.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	N $\frac{1}{16}$ S 31   S 32 1964
	from which
	A fir, 10 ins. diam., bears S. $77^{\circ}$ E., $73\frac{1}{2}$ lks. dist., mkd. N $\frac{1}{16}$ S32 BT.
	A fir, 20 ins. diam., bears N. $55^{\circ}$ W., $66\frac{1}{2}$ lks. dist., mkd. N $\frac{1}{16}$ S31 BT.
	Ascend 95 ft. over SW. slope, along a barbed wire fence.
61.50	Leave pasture land; enter heavy young timber and dense undergrowth, edge bears E. and W.
69.00	SE. cor. of timber; continue along W. edge of logged area.
75.80	Top of ascent, slopes W.; desc. 20 ft. over NW. slope.