

## County Surveyor's Record, Douglas County, Oregon

## Dependent Resurvey, Subdivisional Lines, T. 28 S., R. 8 W.

CHAINS 80.60	<p>The cor. of secs. 29, 30, 31, and 32, perpetuated and recorded by H. L. Eppstein, County Surveyor, in 1924, from an original bearing tree which is no longer in existence, monumented with an iron pipe, <math>\frac{3}{4}</math> in. diam., 4 ins. above ground, firmly set, from which bearing trees marked by Eppstein:</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 81° E., 8 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 16° E., 20 lks. dist., with healed and partially opened double blaze.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 43° W., 12½ lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 50° W., 5½ lks. dist., with healed double blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 28 S R 8 W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 30</td> <td style="padding: 0 5px;">S 29</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 31</td> <td style="padding: 0 5px;">S 32</td> </tr> </table> <p>1964</p> </div> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 33° E., 30 lks. dist., mkd. T28S R8W S32 BT.</p> <p style="padding-left: 40px;">Reset iron pipe alongside the iron post.</p> <p>Corner is located at the end of a barbed wire fence, which extends south.</p> <p>Land, gently rolling. Soil, rocky clay loam. Timber, fir, cedar, hemlock, oak, maple, ash, dogwood, alder, yew, madrone, chinquapin, and cascara; undergrowth, vine maple, hazel, manzanita, ocean spray, huckleberry, blackberry, rhododendron, Oregon grape, fern, and salal.</p>	S 30	S 29	S 31	S 32
S 30	S 29				
S 31	S 32				
7.10	<p>S. 89° 25' W., bet. secs. 30 and 31.</p> <p>Descend 60 ft. over general W. slope, along the S. edge of logged area, through heavy timber and dense undergrowth.</p> <p>Estes Creek, 5 lks. wide, course S.; asc. 80 ft. over SE. slope.</p>				
14.00	<p>Spur, slopes SE.; desc. 20 ft. over SW. slope.</p>				
18.00	<p>Ravine, drains SE.; asc. 45 ft. over SE. slope.</p>				
21.50	<p>Spur, slopes S.; desc. 70 ft. over SW. slope.</p>				
26.15	<p>Dirt road, 15 lks. wide, bears N. 20° W. and S. 30° E.</p>				
29.40	<p>Creek, 3 lks. wide, course S. 10° W.; asc. 65 ft. over SE. slope.</p>				
34.00	<p>Spur, slopes S.; desc. 30 ft. over SW. slope.</p>				
35.00	<p>Ravine, drains S. 10° E.; asc. 85 ft. over SE. slope.</p>				
40.10	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence</p>				