

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 31, T. 28 S., R. 8 W.

CHAINS

The following subdivision of section 31 was executed in conformity with legal surveying practice. The record of true line notes only, is set forth in the following field notes.

From the $\frac{1}{4}$ sec. cor. of secs. 6 and 31, on the S. bdy. of the Tp.

N. $0^{\circ} 02' W.$, on the N. and S. center line of sec. 31.

Ascend 5 ft. over gentle S. slope, across logged area, through scattering young timber and undergrowth.

- 0.38 Gravelled road, 25 lks. wide, bears E. and W.
 3.70 Gravelled road, 15 lks. wide, bears NW. and SE.
 12.40 Lake Creek, 6 lks. wide, course S. $60^{\circ} E.$; asc. 25 ft. over gentle S. slope.
 14.00 Enter heavy second growth timber and dense undergrowth, edge bears E. and W.
 20.11 Point for the center S $1/16$ sec. cor. of sec. 31.
 Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

C
 S $1/16$ | S 31
 C
 1964

from which

A white fir, 10 ins. diam., bears N. $43\frac{1}{2}^{\circ} E.$, 30 lks. dist., mkd. CS $1/16$ S31 BT.

A white fir, 25 ins. diam., bears N. $62^{\circ} W.$, 56 lks. dist., mkd. CS $1/16$ S31 BT.

Ascend 30 ft. over gentle S. slope.

- 40.22 Point for the center $\frac{1}{4}$ sec. cor. of sec. 31, at intersection with the E. and W. center line.
 Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 28 S R 8 W
 C $\frac{1}{4}$ S 31
 1964

from which

A fir, 7 ins. diam., bears N. $44\frac{1}{2}^{\circ} E.$, 77 lks. dist., mkd. C $\frac{1}{4}$ S31 BT.

A fir, 10 ins. diam., bears N. $16^{\circ} W.$, 43 lks. dist., mkd. C $\frac{1}{4}$ S31 BT.

Ascend 85 ft. over S. slope.

- 40.70 SE. corner of pasture land, continue along E. edge of pasture.
 42.48 Dirt road, 15 lks. wide, bears N. $20^{\circ} W.$ and S. $30^{\circ} E.$