

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 31, T. 28 S., R. 8 W.

CHAINS	
54.50	Spur, slopes SE.; desc. 75 ft. over NE. slope; also NE. corner of pasture land; enter logged area with scattering timber and dense undergrowth.
57.60	Creek, 1 lk. wide, course SE.; asc. 45 ft. over SW. slope.
60.33	Point for the center N 1/16 sec. cor. of sec. 31. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	C N 1/16 S 31 C 1964
	from which A fir, 15 ins. diam., bears N. 25° E., 98 lks. dist., mkd. CN 1/16 S31 BT. A white fir, 10 ins. diam., bears N. 53° W., 67½ lks. dist., mkd. CN 1/16 S31 BT. From this point an iron pipe, 1½ ins. diam., 5 ins. above the ground, firmly set, bears S. 86° 45' W., 0.45 chs. dist.
	Leave logged area, edge bears E. and W.; enter heavy timber and dense undergrowth.
	Ascend 100 ft. over SW. slope.
71.00	Spur, slopes SE.; asc. 20 ft. over SE. slope.
76.80	Ravine, drains S. 30° E.; asc. 20 ft. over SW. slope.
80.44	The ¼ sec. cor. of secs. 30 and 31.
	From the ¼ sec. cor. of secs. 31 and 32.
	S. 89° 32' W., on the E. and W. center line of sec. 31.
	Descend 10 ft. over W. slope, across open pasture land.
0.80	Estes Creek, 6 lks. wide, course S.; asc. 105 ft. over gradual E. slope.
12.20	Upper Camas Road, asphaltic, 20 lks. wide, bears N. 40° E. and S. 40° W.; enter logged area with heavy young timber and dense undergrowth.
18.60	Top of ascent, slopes N.; desc. 60 ft. over NW. slope.
28.00	Slope changes to SW.; desc. 25 ft. over SW. slope.
30.10	Dirt road, 15 lks. wide, bears N. 20° E. and S. 10° E.
33.63	Creek, 3 lks. wide, course S.; asc. 35 ft. over SE. slope.
38.25	Dirt road, 15 lks. wide, bears N. 30° W. and S. 30° E.
40.13	The center ¼ sec. cor. of sec. 31. Ascend 35 ft. over SE. slope.
50.75	Top of ascent, slopes S.; desc. 55 ft. over SW. slope.