

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 31, T. 28 S., R. 8 W.

CHAINS

- 59.75 Lake Creek, 4 lks. wide, course S. 40° E.; asc. 5 ft. over E. slope.
- 60.15 Point for the center W 1/16 sec. cor. of sec. 31.
- Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
- $$\begin{array}{c} \text{C} \text{---} \frac{\text{W } 1/16}{\text{S } 31} \text{---} \text{C} \\ 1964 \end{array}$$
- from which
- A fir, 38 ins. diam., bears N. 57° W., 39½ lks. dist., mkd. CW 1/16 S31 BT.
- A cedar, 35 ins. diam., bears S. 29° W., 68 lks. dist., mkd. CW 1/16 S31 BT.
- Ascend 140 ft. over E. slope, changing to NE. slope.
- 65.02 Dirt road, 15 lks. wide, bears N. and S.
- 66.46 Dirt road, 15 lks. wide, bears NW. and SE.
- 81.35 The ¼ sec. cor. of secs. 31 and 36, monumented with an iron post, 2½ ins. diam., 2 ins. above ground, firmly set with brass cap marked and witnessed as described in the official record of the 1959 resurvey.

From the N 1/16 sec. cor. of secs. 31 and 32.

S. 89° 27' W., on the E. and W. center line of the NE¼ of sec. 31.

Descend 40 ft. over SW. slope, across pasture land.

- 0.06 Barbed wire fence, bears N. and S.
- 0.51 Barbed wire fence, bears N. and S.
- 10.43 Estes Creek, 8 lks. wide, course S.; asc. 75 ft. over NE. slope, changing to E. slope, also enter old logged area with heavy young timber and dense undergrowth.
- 11.68 Barbed wire fence, bears N. and S.
- 22.53 Top of ascent, slopes S.; desc. 45 ft. over SW. slope.
- 24.13 Dirt road, 15 lks. wide, bears N. 30° E. and SW.
- 26.18 SE. cor. of timber, also creek, 3 lks. wide, course S. 10° W.; asc. 55 ft. over broken SE. slope, along the N. edge of logged area.
- 37.00 Spur, slopes S.; desc. 15 ft. over SW. slope.
- 40.10 The center N 1/16 sec. cor. of sec. 31.

From the S 1/16 sec. cor. of secs. 31 and 32.

S. 89° 36' W. on the E. and W. center line of the SE¼ of sec. 31.