

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 31, T. 28 S., R. 8 W.

CHAINS

Descend 100 ft. over broken NW. slope, across logged area, through heavy young timber and dense undergrowth.

6.82 Dirt road, 15 lks. wide, bears N. 75° E. and S. 75° W.

16.90 Middle Fork of Coquille River, 6 lks. wide, course S.; asc. 20 ft. over E. slope.

20.00 Top of ascent, slopes S. 20° E.; desc. 15 ft. along broken S. slope.

27.02 Creek, 3 lks. wide, course SE.; asc. 40 ft. along S. slope.

28.85 Upper Camas Road, asphaltic, 25 lks. wide, bears NE. and S. 30° W.

29.15 Barbed wire fence, bears NE. and S. 30° W.

40.15 The center S 1/16 sec. cor. of sec. 31.

From the W 1/16 sec. cor. of secs. 6 and 31, on S. bdy. N. 0° 05' E., on the N. and S. center line of the SW $\frac{1}{4}$ of sec. 31.

Ascend 60 ft. over SE. slope, along W. edge of logged area, through heavy timber and dense undergrowth.

0.60 Gravelled road, 25 lks. wide, bears E. and W.

11.25 Top of ascent, slopes E.; desc. 35 ft. over NE. slope.

19.30 Bottom of descent, slopes SE.; asc. 10 ft. over S. slope.

20.07 Point for the SW 1/16 sec. cor. of sec. 31 at intersection with the E. and W. center line of the SW $\frac{1}{4}$.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

SW 1/16 S31
1964

from which

A white fir, 15 ins. diam., bears N. 62° E.,
66 lks. dist., mkd. SW 1/16 S31 BT.

A white fir, 28 ins. diam., bears N. 45° W.,
37 $\frac{1}{2}$ lks. dist., mkd. SW 1/16 S31 BT.

Ascend 2 ft. over S. slope, across logged area, through heavy young timber and dense undergrowth.

26.67 Dirt road, 15 lks. wide, bears N. 60° W. and S. 60° E.

37.80 Top of ascent, slopes SE.; desc. 10 ft. over NE. slope.

40.17 The center W 1/16 sec. cor. of sec. 31.

From the center S 1/16 sec. cor. of sec. 31.

S. 89° 34' W., on the E. and W. center line of the SW $\frac{1}{4}$ of sec. 31.