

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 31, T. 28 S., R. 8 W.

CHAINS	
	Descend 10 ft. along S. slope, across logged area, through heavy young timber and dense undergrowth.
4.97	Lake Creek, 6 lks. wide, course SE.; asc. 35 ft. along S. slope.
13.85	Dirt road, 15 lks. wide, bears N. 35° W. and S. 35° E.
20.05	The SW 1/16 sec. cor. of sec. 31. Ascend 155 ft. along S. slope, changing to SE. slope, through heavy timber and dense undergrowth.
35.00	Spur, slopes SE.; desc. 35 ft. over SW. slope.
41.28	The S 1/16 sec. cor. of secs. 31 and 36, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., 4 ins. above ground, firmly set, with brass cap marked and witnessed as described in the official record. (1959)
	From the center W 1/16 sec. cor. of sec. 31. N.0° 06' W., on the N. and S. center line of the NW¼ of sec. 31. Descend 5 ft. over NE. slope, across logged area, through heavy young timber and dense undergrowth.
0.55	Lake Creek, 4 lks. wide, course S. 40° E.; asc. 135 ft. over S. slope.
13.00	Top of ascent, slopes W.; desc. 15 ft. over NW. slope.
15.00	Ravine, drains S. 60° W.; asc. 55 ft. over S. slope, changing to SW. slope.
20.07	Point for the NW 1/16 sec. cor. of sec. 31 at intersection with the E. and W. center line of the NW¼. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	NW 1/16 S31 1964
	from which A fir, 10 ins. diam., bears S. 40° E., 34 lks. dist., mkd. NW 1/16 S31 BT. A cedar, 12 ins. diam., bears S. 11½° W., 142 lks. dist., mkd. NW 1/16 S31 BT.
	Ascend 15 ft. over SW. slope.
21.50	Spur, slopes S. 40° W.; desc. 10 ft. over NW. slope.
22.10	Dirt road, 15 lks. wide, bears NE. and SW.
24.00	Ravine, drains W.; asc. 75 ft. over SW. slope.
30.65	Dirt road, 15 lks. wide, bears N. 10° W. and S. 20° E. also top of ascent, slopes W.; desc. 10 ft. over NW. slope.
34.50	Ravine, drains W.; asc. 35 ft. over S. slope.