

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of W. Bdy., T. 30 S., R. 6 W.

CHAINS

and bearing trees marked by Byron

A fir, 13 ins. diam., bears N. 20° E., 24 lks. dist., with illegible scribe marks visible on partially healed double blaze.

A fir, 10 ins. diam., bears S. 29° E., 40 lks. dist., with illegible scribe marks visible on partially healed double blaze.

A fir, 9 ins. diam., bears S. 23° W., 27 lks. dist., with illegible scribe marks visible on partially healed double blaze.

A fir, 15 ins. diam., bears N. 18° W., 65 lks. dist., with illegible scribe marks visible on partially healed double blaze.

Add marks BLM 1964 to bottom of brass cap.

N. 0° 40' E., bet. secs. 7 and 12, along the W. bdy. of Tp., marking and blazing the true line.

Ascend 25 ft. over SE. slope, through heavy timber and dense undergrowth.

- 1.60 Ravine, drains S. 40° E.; asc. 110 ft. over SW. slope.
- 4.70 Spur, slopes S. 30° E.; asc. 130 ft. over SE. slope.
- 11.00 Spur, slopes S. 50° W.; desc. 130 ft. over NW. slope.
- 20.50 Ravine, drains S. 50° W.; asc. 415 ft. over broken SE. slope.
- 38.00 Spur, slopes W.; desc. 2 ft. over NW. slope.
- 38.96 The  $\frac{1}{4}$  sec. cor. of secs. 7 and 12, perpetuated and recorded by J. W. Byron, Deputy County Surveyor, in 1963, monumented with an iron pipe, 1 in. diam., 16 ins. above the ground, firmly set, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S  
R S 12 | S 7 R  
7            6  
W    1963    W

from which the remaining original bearing tree

A down oak, 10 ins. diam., bears N. 50° E., 128 $\frac{1}{2}$  lks. dist., with scribe marks S BT and other fragmentary marks visible on opened blaze. (Record distance, 130 lks.)

and bearing trees marked by Byron

A fir, 15 ins. diam., bears N. 33° E., 11 lks. dist., with scribe marks  $\frac{1}{4}$  S7 CS BT visible on double blaze.

A fir, 10 ins. diam., bears S. 18° W., 23 $\frac{1}{2}$  lks. dist., with scribe marks  $\frac{1}{4}$  S12 CS BT visible on double blaze.

Add marks BLM 1964 to bottom of brass cap.

Corner is at the SE. corner of a logged area.