

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of W. Bdy., T. 30 S., R. 6 W.

CHAINS

N. 0° 08' W., beginning new measurement.

Descend 45 ft. over NW. slope, along the E. edge of a logged area, through heavy timber and dense undergrowth.

- 0.33 Barbed wire fence, bears E. and W.
- 1.80 Ravine, drains S. 70° W.; asc. 95 ft. over SW. slope.
- 8.00 Spur, slopes S. 70° W.; desc. 10 ft. over NW. slope.
- 9.40 Ravine, drains SW.; asc. 110 ft. over SW. slope.
- 15.70 Ridge, bears N. 60° W. and S. 60° E.; desc. 75 ft. over N. slope.
- 19.94 Point for the N 1/16 sec. cor. of secs. 7 and 12.
- Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

N 1/16
S 12 | S 7
1964

from which

A fir, 15 ins. diam., bears S. 63° E., 46½ lks. dist., mkd. N1/16 S7 BT.

A fir, 13 ins. diam., bears S. 74° W., 43 lks. dist., mkd. N1/16 S12 BT.

Descend 130 ft. over N. slope, changing to NE. slope.

- 28.50 Ravine, drains N. 60° E.; asc. 15 ft. over SE. slope.
- 30.80 Spur, slopes N. 60° E.; desc. 70 ft. over NE. slope.
- 36.10 Ravine, drains E.; asc. 95 ft. over SE. slope.
- 39.88 The cor. of secs. 1, 6, 7, and 12, perpetuated and recorded by J. W. Byron, Deputy County Surveyor, in 1963, monumented with an iron pipe, 1 in. diam., 14 ins. above the ground, firmly set, with brass cap mkd.

COUNTY SURVEYORS OFFICE

R T 30 S R
7 S 1 | S 6 6
W S 12 | S 7 W

1963

from which the original bearing trees

A madrone, 34 ins. diam., bears N. 49° E., 106 lks. dist., with healed blaze. (Record bearing and distance, N. 45° E., 104 lks.)

A madrone, 34 ins. diam., bears S. 82° E., 125 lks. dist., with illegible scribe marks visible on partially healed blaze. (Record bearing and distance, S. 87° E., 123 lks.)

A dead madrone, 22 ins. diam., bears S. 3° W., 63 lks. dist., with illegible scribe marks visible on opened blaze.