

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of W. Bdy., T. 30 S., R. 6 W.

CHAINS

A pine, 48 ins. diam., bears N. 45° W., 16 lks. dist., with scribe marks T30 R7W S1 BT visible on partially healed double blaze. (Record distance, 12 lks.)

and bearing trees marked by Byron

A white fir, 10 ins. diam., bears N. 81° E., 8½ lks. dist., with scribe marks T30S R6W S6 CS BT visible on double blaze.

A fir, 9 ins. diam., bears S. 25° E., 34 lks. dist., with illegible scribe marks visible on partially healed double blaze.

A white fir, 13 ins. diam., bears S. 58° W., 32½ lks. dist., with scribe marks T30S R7W S12 CS BT visible on double blaze.

Add marks BLM 1964 to bottom of brass cap.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, white fir, pine, cedar, yew, madrone, oak, maple, ash, and chinquapin; undergrowth, fern, salal, Oregon grape, hazel, ocean spray, vine maple, and blackberry.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 30 S., R. 6 W., Willamette Meridian, Oregon

(Restoring the 1855 survey by Addison R. Flint)

From the cor. of secs. 7, 8, 17, and 18, perpetuated and recorded by M. E. Godfrey, Deputy County Surveyor, in 1964, monumented with an iron pipe, 1 in. diam., 12 ins. above the ground, firmly set, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S
S 7 | S 8
S 18 | S 17
R 6 W
1964

from which the remaining original bearing trees

A sawed fir stump, 24 ins. diam., bears S. 5° W., 51 lks. dist., with scribe marks 7 BT visible on opened blaze. (Record bearing, S. 35° E.)

A fir, 45 ins. diam., bears N. 83° W., 181 lks. dist., with illegible scribe marks visible on opened blaze. (Record bearing and distance, S. 89° W., 185 lks.)

A dead fir, 43 ins. diam., bears N. 36½° W., 176½ lks. dist., with scribe marks S R6W S visible on opened blaze. (Record bearing and distance, N. 40° W., 175 lks.)

and new bearing trees

A fir, 13 ins. diam., bears N. 34½° E., 197 lks. dist., mkd. T30S R6W S8 BT.