

Dependent Resurvey, Subdivisional Lines, T. 30 S., R. 6 W.

CHAINS

A fir, 23 ins. diam., bears S. 53° E., 72 lks. dist., mkd. T30S R6W S17 BT.

A cedar, 21 ins. diam., S 53° W., 68 lks. dist., mkd. T30S R6W S18 BT.

Add marks BLM 1964 to bottom of the brass cap.

From this point an iron pipe, 1 in. diam., 6 ins. above ground, firmly set in concrete, bears N. 42° 30' W., 0.545 chs. dist., with brass cap mkd. T30S R6W 7-8-17-18 2880 1957, from which bearing trees marked in 1943:

A fir, 60 ins. diam., bears N. 50° E., 51½ lks. dist., with scribe marks T30S R6W S8 CS BT visible on bark blaze.

A madrone snag, 15 ins. diam., bears S. 58° E., 24½ lks. dist., with scribe marks S17 T30S R6W CS BT visible on open double blaze.

A fir, 15 ins. diam., bears S. 44° W., 11½ lks. dist., with healed blaze.

and bearing trees marked in 1957

A fir, 14 ins. diam., bears S. 17° E., 63½ lks. dist., with illegible scribe marks visible on partially healed double blaze.

A fir, 13 ins. diam., bears S. 33° W., 27½ lks. dist., with scribe marks 8S visible on partially healed blaze and BT visible on bark blaze at base.

A cedar, 18 ins. diam., bears N. 83½° W., 48 lks. dist., with scribe marks S18 R6W BT visible on partially healed double blaze.

A fir, 9 ins. diam., bears N. 21° W., 38½ lks. dist., with scribe marks S R6W BT visible on partially healed double blaze.

N. 88° 33' W., bet. secs. 7 and 18, marking and blazing the true line.

Descend 190 ft. over NW. slope, through heavy timber and dense undergrowth.

11.40 Ravine, drains N.; asc. 120 ft. over NE. slope.

16.00 Spur ridge, bears N. 30° W. and S. 30° E.; desc. 530 ft. over NW. slope changing to W. slope.

34.00 Ravine, drains N. 60° W.; desc. 125 ft. over NW. slope.

40.62 The ¼ sec. cor. of secs. 7 and 18, determined at record bearing and distance from the remaining original bearing tree:

A fir, 42 ins. diam., bears N. 15° W., 17 lks. dist., with scribe marks S and other illegible marks visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.