

Dependent Resurvey, Subdivisional Lines, T. 30 S., R. 6 W.

CHAINS	
	Descend 210 ft. over NW. slope, across logged area through scattering timber and dense undergrowth.
55.90	Creek, 2 lks. wide, course N. 30° W.; asc. 40 ft. over E. slope, changing to SE. slope.
59.46	Point for the W 1/16 sec. cor. of secs. 6 and 7. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> $W \frac{1}{16} \frac{S \ 6}{S \ 7}$ 1964 </div> from which <div style="margin-left: 40px;"> A fir, 14 ins. diam., bears N. 35½° W., 157 lks. dist., mkd. W 1/16 S6 BT. A fir, 10 ins. diam., bears S. 16° W., 194½ lks. dist., mkd. W 1/16 S7 BT. </div> Ascend 70 ft. over SE. slope.
65.30	Top of ascent, slopes N. 35° E.; desc. 10 ft. over NW. slope.
68.20	Ravine, drains N. 35° E.; asc. 220 ft. over SE. slope.
82.03	The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp. Land, mountainous. Soil, rocky clay loam. Timber, fir, white fir, pine, cedar, yew, madrone, oak, alder, and maple; undergrowth, fern, salal, vine maple, Oregon grape, ocean spray, hazel, and black-berry.
Subdivision of Section 7 T. 30 S., R. 6 W., Willamette Meridian, Oregon	
The following subdivision of section 7 was executed in conformity with legal surveying practice. The record of true line notes, only, is set forth in the following field notes.	
	<hr/> From the ¼ sec. cor. of secs. 7 and 18.
	N. 0° 52' E., on the N. and S. center line of sec. 7.
	Descend 70 ft. over NW. slope, through heavy timber and dense undergrowth.
2.00	Ravine, drains S. 80° W.; asc. 100 ft. over SW. slope.
5.50	Ravine, drains S. 40° W.; asc. 305 ft. over general S. slope.
19.05	Dirt road, 25 lks. wide, bears E. and W.
20.30	Ridge, bears N. 60° W. and S. 60° E.; desc. 325 ft. over broken NE. slope.
24.55	Dirt road, 25 lks. wide, bears N. 60° W. and S. 60° E.