

13591 County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 7, T. 30 S., R. 6 W.

CHAINS

- 12.80 Spur, slopes N. 15° W.; desc. 140 ft. over broken NW. slope.
- 19.80 Ravine, drains N. 20° W.; asc. 25 ft. over NE. slope.
- 23.00 Spur, slopes NW.; desc. 345 ft. over broken SW. slope.
- 39.42 The center $\frac{1}{4}$ sec. cor. of sec. 7.
Descend 100 ft. over SW. slope.
- 44.15 Creek, 2 lks. wide, course NW.; asc. 240 ft. over broken NE. slope.
- 58.89 Point for the center W 1/16 sec. cor. of sec. 7.
Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

C — W 1/16 — C
S 7
1964

from which

A fir, 45 ins. diam., bears N. 86 $\frac{1}{2}$ ° E., 141 lks. dist., mkd. CW 1/16 S7 BT.

A fir, 10 ins. diam., bears S. 79 $\frac{1}{2}$ ° W., 201 lks. dist., mkd. CW 1/16 S7 BT.

Ascend 125 ft. over NE. slope.

- 59.28 Dirt road, 25 lks. wide, bears N. 60° W. and S. 60° E.
- 70.00 Ridge, bears N. 30° W. and S. 30° E.; desc. 40 ft. over SW. slope.
- 74.70 Spur, slopes S. 80° W.; desc. 135 ft. over W. slope, changing to NW. slope.
- 81.07 The $\frac{1}{4}$ sec. cor. of secs. 7 and 12, on W. bdy. of the Tp.

From the center W 1/16 sec. cor. of sec. 7.

N. 0° 23' E., on the N. and S. center line of the NW $\frac{1}{4}$ of sec. 7.

Descend 110 ft. over NE. slope, through heavy timber and dense undergrowth.

- 4.00 Ravine, drains N. 75° E.; asc. 135 ft. over SE. slope.
- 11.20 Spur, slopes S. 75° E.; desc. 140 ft. over NE. slope.
- 19.96 Point for the NW 1/16 sec. cor. of sec. 7, at intersection with the E. and W. center line of the NW $\frac{1}{4}$.
Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

NW 1/16 S7
1964

from which