

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 30 S., R. 8 W.

CHAINS

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 12 ins. in the ground, to solid rock, and supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 30 S R 8 W

$$S 11 \frac{1}{4} S 12$$

1964

from which new bearing trees

A fir, 20 ins. diam., bears N.  $38\frac{1}{4}^{\circ}$  E., 80 lks. dist., mkd.  $\frac{1}{4}$  S12 BT.

A fir, 10 ins. diam., bears S.  $73\frac{1}{2}^{\circ}$  W.,  $36\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S11 BT.

---

N.  $1^{\circ} 27'$  E., beginning new measurement.

Ascend 130 ft. over S. slope.

3.95 Spur, slopes E.; desc. 70 ft. over NE. slope.

17.35 Draw, drains E.; asc. 85 ft. over broken SE. slope.

31.45 Top of ascent, slopes E.; desc. 10 ft. over NE. slope.

37.15 Wet ravine, drains S.  $30^{\circ}$  E.; asc. 40 ft. over SW. slope.

39.63 The cor. of secs. 1, 2, 11, and 12, determined at record bearing and distance from the remains of the original bearing trees:

A madrone, 23 ins. diam., bears N.  $24^{\circ}$  E., 23 lks. dist., with no mks. visible.

A sawed fir stump, 36 ins. diam., bears S.  $17^{\circ}$  E., 41 lks. dist., with a healed blaze.

A madrone snag, 10 ins. diam., bears S.  $64^{\circ}$  W., 31 lks. dist., with visible scribe mks. on open blaze.

A down chinquapin, 12 ins. diam., bears N.  $68^{\circ}$  W., 39 lks. dist., with old axe mks. visible on open blaze.

and local bearing trees

A fir, 7 ins. diam., bears S.  $81^{\circ}$  E., 50 lks. dist., mkd. S12 T30S R8W BT on double blaze.

A hemlock, 19 ins. diam., bears S.  $44\frac{1}{4}^{\circ}$  W., 57 lks. dist., with a partially healed double blaze.

A hemlock, 18 ins. diam., bears N.  $84^{\circ}$  W., 51 lks. dist., mkd. S2 T30S R8W BT on double blaze.

At the corner point