

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 30 S., R. 8 W.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 30 S R 8 W
S 2 S 1
S 11 S 12
1964

from which a new bearing tree

A fir, 10 ins. diam., bears N. $40\frac{1}{4}^{\circ}$ E., 65 lks. dist., mkd. T30S R8W S1 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, cedar, hemlock, madrone, maple, alder, dogwood, chinquapin, yew and live oak; undergrowth, salal, Oregon grape, hazel, arrowwood, manzanita, poison oak, huckleberry, live oak, vine maple, ferns and vines.

From the cor. of secs. 14, 15, 22, and 23, determined at record bearing and distance from the remains of the original bearing trees:

A sawed fir stump, 38 ins. diam., bears N. 44° E., 44 lks. dist., with T3 and other illegible scribe mks. on bark detached from stump.

A fir, 45 ins. diam., bears S. 35° E., 23 lks. dist., mkd. T30S R8W S23 BT on bark blaze.

A rotted fir stump, size indeterminate, bears S. 48° W., 38 lks. dist., with no mks. remaining.

A rotted fir stump, 28 ins. diam., bears N. 14° W., 42 lks. dist., with no mks. remaining.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 30 S R 8 W
S 15 S 14
S 22 S 23
1964

from which new bearing trees

A fir, 10 ins. diam., bears N. $80\frac{1}{2}^{\circ}$ E., 117 lks. dist., mkd. T30S R8W S14 BT.

A fir, 20 ins. diam., bears S. 26° W., 83 lks. dist., mkd. T30S R8W S22 BT.

A fir, 8 ins. diam., bears N. $81\frac{1}{2}^{\circ}$ W., 41 lks. dist., mkd. T30S R8W S15 BT.

N. $1^{\circ} 05'$ W., bet. secs. 14 and 15.

Descend 385 ft. over NW. slope, along W. edge of logged area, edge bears N. and E.

26.50

Ravine, drains S. 65° W.; asc. 45 ft. over SW. slope.