

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 11, T. 30 S., R. 8 W.

CHAINS

A maple, 6 ins. diam., bears N. $52\frac{1}{4}^{\circ}$ E., 39 lks. dist., mkd. CS 1/16 S11 BT.

A maple, 8 ins. diam., bears S. 85° E., 115 lks. dist., mkd. CS 1/16 S11 BT.

No suitable live bearing tree available within limits to the W.

Ascend 45 ft. over SE. slope.

21.75 Spur, slopes S. 35° W.; asc. 185 ft. over SW. slope.

31.90 Enter timber, edge bears S. 20° E. and SW.

39.44 Point for the center $\frac{1}{4}$ sec. cor. of sec. 11, at intersection with the E. and W. center line.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

C $\frac{1}{4}$ S 11
1964

from which

A fir, 6 ins. diam., bears S. $1\frac{1}{2}^{\circ}$ E., 64 lks. dist. mkd. C $\frac{1}{4}$ S11 BT.

A fir, 23 ins. diam., bears N. $55\frac{1}{2}^{\circ}$ W., 26 lks. dist., mkd. C $\frac{1}{4}$ S11 BT.

Ascend 135 ft. over SW. slope.

51.25 Enter logged area, edge bears N. 15° W. and S. 15° E.

52.45 Spur, slopes S. 15° E.; desc. 95 ft. over NE. slope.

53.40 Enter timber, edge bears E. and W.

56.35 Ravine, drains S. 75° E.; asc. 295 ft. over SW. slope, changing to S. slope.

76.50 Ridge, bears E. and W.; desc. 95 ft. over N. slope.

78.92 The $\frac{1}{4}$ sec. cor. of secs. 2 and 11.

From the $\frac{1}{4}$ sec. cor. of secs. 11 and 12.

S. $88^{\circ} 11'$ W., on the E. and W. center line of sec. 11.

Descend 75 ft. along S. slope, changing to SW. slope, through heavy timber and light undergrowth.

14.00 Enter logged area, edge bears N. and S. 60° W.

15.25 Ravine, drains S. 20° E.; asc. 35 ft. over NE. slope.

19.36 Point for the center E 1/16 sec. cor. of sec. 11.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

C $\frac{E 1/16}{S 11}$ C
1964

from which