

County Surveyor's Record, Douglas County, Oregon

T. 30 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir, 16 ins. diam., bears S. 62° W., 31 lks. dist., mkd. $\frac{1}{4}$ S32 BT.

The cor. of secs. 28, 29, 32 and 33, determined at record distance from the remaining original bearing trees:

A madrone, 20 ins. diam., bears N. 16° E., 15 lks. dist., mkd. BT, on an opened blaze. (Record, N. 20° E.)

A dead chinquapin, 8 ins. diam., bears N. 50° W., 31 lks. dist., mkd. 0, on a badly decayed blaze. (Record, N. 48° W.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap marked

T 30 S R 8 W
S 29 S 28
S 32 S 33
1963

from which new bearing trees

A fir, 14 ins. diam., bears N. $3\frac{1}{2}^{\circ}$ E., 68 lks. dist., mkd. T30S R8W S28 BT.

A fir, 9 ins. diam., bears S. 68° E., 40 lks. dist., mkd. T30S R8W S33 BT.

A fir, 11 ins. diam., bears S. $32\frac{1}{2}^{\circ}$ W., 44 lks. dist., mkd. T30S R8W S32 BT.

A fir, 8 ins. diam., bears N. $32\frac{1}{2}^{\circ}$ W., 12 lks. dist., mkd. T30S R8W S29 BT.

The corner is situated on a W. slope, 40 lks. E. of a creek, 3 lks. wide, course N. 10° W.

The $\frac{1}{4}$ sec. cor. of secs. 28 and 33, determined at record bearing and distance from the original bearing trees:

A fir, 8 ins. diam., down and greatly decayed, bears N. 54° E., 18 lks. dist., no marks remain.

A fir, 9 ins. diam., bears S. 26° E., 17 lks. dist., mkd. $\frac{1}{4}$ S BT, on opened blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

$\frac{1}{4}$ S 28
S 33
T 30 S R 8 W
1963

from which new bearing trees