

County Surveyor's Record, Douglas County, Oregon

Remonumentation T. 30 S., R. 8 W., Will. Meridian, Oregon

CHAINS

The following field notes describe the remonumentation of certain original corner points of Township 30 South, Range 8 West, of the Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group No. 350, Oregon, Dated May 8, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points, With New Accessories When Needed".

Remonumentation of Certain Original Corner Points,
T. 30 S., R. 8 W., Willamette Meridian, Oregon
(Remonumenting the corners established by
William H. Byars, in 1882)

The $\frac{1}{4}$ sec. cor. of secs. 32 and 33, determined at record bearing and distance from the remaining original bearing tree:

A fir, 18 ins. diam., bears S. 35° W., 18 lks.
dist., mkd. $\frac{1}{4}$ S B, on opened blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

$\frac{1}{4}$
S 32/S 33
T 30 S R 8 W
1963

from which new bearing trees

A cedar, 9 ins. diam., bears N. 81° E., 43 lks.
dist., mkd. $\frac{1}{4}$ S33 BT.

A fir, 16 ins. diam., bears S. 62° W., 31 lks.
dist., mkd. $\frac{1}{4}$ S32 BT.

The cor. of secs. 28, 29, 32 and 33, determined at record distance from the remaining original bearing trees:

A madrone, 20 ins. diam., bears N. 16° E., 15 lks.
dist., mkd. BT, on an opened blaze. (Record,
N. 20° E.)

A dead Chinquapin, 8 ins. diam., bears N. 50° W.,
31 lks. dist., mkd. "O", on a badly decayed blaze.
Records, N. 48° W.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap marked

T 30 S R 8 W
S 29 | S 28
S 32 | S 33
1963

from which new bearing trees.

A fir, 14 ins. diam., bears N. $3\frac{1}{2}^{\circ}$ E., 68 lks.
dist., mkd. T30S R8W S28 BT