

County Surveyor's Record, Douglas County, Oregon

T. 30 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir, 9 ins. diam., bears S. 68° E., 40 lks.
dist., mkd. T30S R8W S33 BT.

A fir, 11 ins. diam., bears S. $32\frac{1}{2}^{\circ}$ W., 44 lks.
dist., mkd. T30S R8W S32 BT.

A fir, 8 ins. diam., bears N. $32\frac{1}{2}^{\circ}$ W., 12 lks.
dist., mkd. T30S R8W S29 BT.

The corner is situated on a W. slope, 40 lks. E. of a creek,
3 lks. wide, course N. 10° W.

The $\frac{1}{4}$ Sec. Cor. of secs. 28 and 33, determined at record
bearing and distance from the original bearing trees:

A fir, 8 ins. diam., down and greatly decayed, bears
N. 54° E., 18 lks. dist., no marks remain.

A fir, 9 ins. diam., bears S. 26° E., 17 lks. dist.,
mkd. $\frac{1}{4}$ S BT, on opened blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in
the ground, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \quad \frac{S \ 28}{S \ 33} \\ T \ 30 \ S \ R \ 8 \ W \\ 1963 \end{array}$$

from which new bearing trees

A fir, 16 ins. diam., bears N. 54° W., 107 lks.
dist., mkd. $\frac{1}{4}$ S28 BT.

A fir, 20 ins. diam., bears S. 71° E. 104 lks.
dist., mkd. $\frac{1}{4}$ S33 BT.

The $\frac{1}{4}$ sec. cor. of secs. 28 and 29, determined at record
bearing and distance from the remains of the original
bearing trees:

A madrone stump, decayed to a mulch, bears
N. 40° E. 8 lks. dist., no marks remain.

A chinquapin, 6 ins. diam., down and greatly decayed,
bears S. 46° W., 40 lks. dist., mkd. with partial
scribing, in reverse, on a fragment of overgrowth.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in
the ground, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ S \ 29 / S \ 28 \\ T \ 30 \ S \ R \ 8 \ W \\ 1963 \end{array}$$

from which new bearing trees

A fir, 11 ins. diam., bears N. 71° E., 9 lks.
dist., mkd. $\frac{1}{4}$ S 28 BT.