

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey Portion of S. Bdy., T. 31 S., R. 7 W.

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd.

T 31 S R 7 W
S 35 S 36
S 2 S 1
T 32 S R 7 W
1964

Reset the iron pipe and cedar post alongside the iron post.

S. $89^{\circ} 20'$ W., bet. secs. 2 and 35, marking and blazing the true line.

Descend 100 ft. over W. slope, through heavy old-growth timber and thin undergrowth.

7.65 Martin Creek, 12 lks. wide, course N.; asc. 290 ft. over NE. slope.

20.10 Point for the E $\frac{1}{16}$ sec. cor. of secs. 2 and 35.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd.

E $\frac{1}{16}$ $\frac{S 35}{S 2}$
1964

from which

A fir, 15 ins. diam., bears N. 1° E., 2 lks. dist., mkd. E $\frac{1}{16}$ S35 BT.A fir, 18 ins. diam., bears S. 59° E., $38\frac{1}{2}$ lks. dist., mkd. E $\frac{1}{16}$ S2 BT.

Ascend 400 ft. over NE. slope.

35.50 Ridge, bears N. 20° W. and S. 20° E.; desc. 170 ft. over SW. slope.40.20 The $\frac{1}{4}$ sec. cor. of secs. 2 and 35, determined at record bearing and distance from the remains of the original bearing trees:A fir, 45 ins. diam., bears N. 10° W., 48 lks. dist., mkd. BT on bark blaze.A rotted live oak stump, size indeterminate, bears S. 55° E., 16 lks. dist., with no mks. remaining.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 31 S R 7 W
$\frac{1}{4}$ $\frac{S 35}{S 2}$
T 32 S R 7 W
1964

from which new bearing trees