

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey Portion of S. Bdy., T. 31 S., R. 7 W.

CHAINS

manzanita, huckleberry, poison oak, hazel, live oak, Oregon grape, arrowwood, young timber, rhododendron, vine maple, ferns, and vines.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 31 S., R. 7 W.
(Restoring the 1882 Survey by William H. Byars)

From the cor. of secs. 1, 2, 35, and 36, on the S.
bdy. of the Tp.

N. 0° 17' W., bet. secs. 35 and 36, marking and blaz-
ing the true line.

Ascend 5 ft. along W. slope, through heavy old-growth
timber and moderate undergrowth.

4.10 Spur, slopes W.; desc. 75 ft. over N. slope.

7.65 Creek, 2 lks. wide, course W.; asc. 150 ft. over S.
slope, changing to SW. slope.

17.75 Spur, slopes W.; desc. 65 ft. over N. slope, changing
to NW. slope.

21.95 Draw, drains W.; asc. 45 ft. over SW. slope.

24.50 Spur, slopes W.; desc. 95 ft. over NW. slope.

32.95 Creek, 1 lk. wide, course N. 30° W.; asc. 20 ft. over
SW. slope.

36.00 Spur, slopes W.; desc. 35 ft. over NW. slope.

39.60 The $\frac{1}{4}$ sec. cor. of secs. 35 and 36, determined at
record bearing and distance from the remaining original
SE. bearing tree,

A fir, 47 ins. diam., bears S. 80° E., 55 lks.
dist., mkd. $\frac{1}{4}$ S BT on a bark blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 31 S R 7 W

S 35 $\frac{1}{4}$ S 36

1964

from which new bearing trees

A fir, 9 ins. diam., bears N. $68\frac{3}{4}$ ° E., $64\frac{1}{2}$ lks.
dist., mkd. $\frac{1}{4}$ S36 BT.

A fir, 14 ins. diam., bears S. $54\frac{3}{4}$ ° W., 29 lks.
dist., mkd. $\frac{1}{4}$ S35 BT.

N. 0° 03' E., beginning new measurement.

Descend 10 ft. over NW. slope.