

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines,  
T. 31 S., R. 7 W.

CHAINS	
	N. 0° 14' E., bet. secs. 26 and 27. Descend 240 ft. over NW. slope, through heavy timber and thin undergrowth.
18.70	Cedar Creek, 7 lks. wide, course S. 70° W.; asc. 55 ft. over SE. slope.
20.20	Dirt road, 20 lks. wide, bears N. 70° E. and S. 70° W.
22.30	Spur, slopes S. 40° E.; desc. 15 ft. over NE. slope.
25.30	Creek, 2 lks. wide, course S. 40° E.; asc. 175 ft. over SE. slope.
40.05	The $\frac{1}{4}$ sec. cor. of secs. 26 and 27, recorded and re-monumented in 1962 by Howard W. Johnstone, Registered Land Surveyor No. 498, with an iron pipe, 1 in. diam., 10 ins. above ground, firmly set, from which the remains of the original bearing trees:  <div style="margin-left: 40px;"> <p>A pine snag, 12 ins. diam., bears N. 18° E., 62 lks. dist., mkd. <math>\frac{1}{4}</math> S BT on opened double blaze.</p> <p>A stump hole, bears S. 12° W., 32 lks. dist. (record distance, 28 lks.)</p> </div> <p>and bearing trees mkd. by Johnstone:</p> <div style="margin-left: 40px;"> <p>A pine, 8 ins. diam., bears S. 43<math>\frac{3}{4}</math>° E., 9 lks. dist., mkd. with a partially healed double blaze.</p> <p>A fir, 25 ins. diam., bears N. 4<math>\frac{1}{2}</math>° W., 32 lks. dist., mkd. with a partially healed double blaze.</p> </div> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 31 S R 7 W</p> <p style="margin-left: 100px;">↑</p> <p style="margin-left: 80px;">S 27   S 26</p> <p style="margin-left: 100px;">1964</p> </div> <p>Reset the iron pipe alongside the iron post.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 0° 20' W., beginning new measurement. Ascend 10 ft. over SE. slope.</p>
2.35	Top of ascent, slopes E.; desc. 30 ft. over NE. slope.
5.90	Creek, 3 lks. wide, course S. 25° E.; asc. 365 ft. over SW. slope.
8.50	Dirt road, 15 lks. wide, bears N. 40° W. and S. 40° E.
22.20	Spur, slopes S. 10° E., from N.; asc. 165 ft. along top of spur.
30.20	Spur, slopes S., from N. 35° W.; asc. 195 ft. along E. slope, changing to SE. slope.
39.77	The cor. of secs. 22, 23, 26, and 27, recorded and re-monumented in 1962 by Howard W. Johnstone, Registered