

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines
T. 31 S., R. 7 W.

CHAINS

Land Surveyor No. 498, with a wooden stake, 4 ft. long, 3 ins. square, firmly set 12 ins. in the ground, from which the remains of the original bearing trees:

A down fir snag, 8 ins. diam., bears N. 36° E., 21 lks. dist., with no mks. visible on opened blaze.

A down fir, 20 ins. diam., bears S. 48° E., 25 lks. dist., mkd. with a healed blaze.

A down fir, 12 ins. diam., bears S. 14° W., 29 lks. dist., with no mks. visible.

A fir, 21 ins. diam., bears N. 68° W., 33 lks. dist., mkd. with a healed blaze.

and bearing trees mkd. by Johnstone:

A fir, 12 ins. diam., bears N. 10½° E., 17 lks. dist., mkd. with a partially healed double blaze.

A fir, 13 ins. diam., bears S. 9½° E., 75 lks. dist., mkd. with a partially healed double blaze.

A fir, 20 ins. diam., bears S. 14° W., 37 lks. dist., mkd. with a partially healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.

T 31 S R 7 W
S 22 | S 23
S 27 | S 26
1964

Reset the wooden stake alongside the iron post.

Land, mountainous.

Soil, rocky clay.

Timber, pine, fir, hemlock, cedar, yew, maple, madrone, and chinquapin; undergrowth, salal, young timber, arrowwood, Oregon grape, live oak, hazel, poison oak, vines, and ferns.

From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp.

N. 1° 51' W., bet. secs. 33 and 34.

Ascend 85 ft. over S. slope, changing to SE. slope, through heavy timber and dense undergrowth.

4.35 Spur, slopes E.; desc. 155 ft. over NE. slope.

12.00 Creek, 1 lk. wide, course E.; asc. 60 ft. over broken SE. slope.

24.10 Spur, slopes E.; desc. 125 ft. over NE. slope.

33.25 Draw, drains E.; asc. 50 ft. over SE. slope.